

TERRAZZO TILE SPECIFICATION SHEET

GENERAL INFORMATION

Product	Terrazzo Tile
Manufacturing	Vibrated, Pressed, Polished
Finish	Honed
Description	Ready-to-install honed terrazzo tile
Application	Suitable for floor or wall placement in high-traffic areas, both interiors, and exteriors. Compatible with various subfloors including Plaster, Hardibacker, Durock, Ditra, etc.

TECHNICAL DATA

Composition	Sand, Marble, Cement, Pigments
Measurements	<ul style="list-style-type: none"> Nominal: 16 x 16 inches (400 x 400 mm) Actual: 397 x 397 mm (+/- 1 mm tolerance)
Thickness	0.7 inches / 18 mm (+/- 1 mm tolerance)
Edge	Straight
Weight	<ul style="list-style-type: none"> 16.5 lbs (7.5 kg) per unit 66 lbs (30 kg) per box
Units per square feet - square meter	10.7 units / ft ² - 6.25 units / m ²
Boxes per pallet	64

LABORATORY TESTS

Wear Resistance	133 (IRAM: ≤ 15 mm)
Water Absorption	5.7% (IRAM: ≤ 10%)
Impact Test	180 (IRAM: ≥ 70 height)
Flexural Strength	596 kg/cm ² (IRAM: ≥ 35 kg/cm ²)

*IRAM: Instituto Argentino de Normalización y Certificación (<https://www.iram.org.ar>)