

# 95STS Single Valve Series Commercial Water Filter

## Nextsand (95STS NX Filter)



Canature WaterGroup™ has dedicated professional engineers with decades of commercial water treatment experience. Over the years, they have built a reputation for designing efficient, high quality commercial water systems.



### Operating Parameters

- Operating pressure: 30 - 125 PSI (206 - 862 KPA)
- Operating temperature: 39 - 100 °F (4 - 38 °C)
- Electrical: Input 120V 60 Hz - Output 12VAC

### Materials of Construction

- Control Valve: Plastic PPO
- Pressure Tanks: Corrosion resistant fibreglass reinforced polyethylene NSF 44 Certified
- Internal Distribution

### Standard Features

- 95 high flow control valve with RWB piston (standard)
- Large display: Fully programmable and easy to set electronic controller
- Inlet/Outlet connection sizes available in 1", 1.25", and 1.5"
- Advanced Diagnostic Information: Easily trouble shoot and access system information displayed in real time
- Optional Auxiliary Contact: activated for regeneration cycle
- Battery Back-up System: In the event of a power outage, the system can continue to meter and monitor water usage for up to 9 hours

**NEXTSAND (95STS NX FILTER)** Remove suspended solids, ferric hydroxide (red water iron) or sediment from your well or water system down to 5 microns. Nextsand has proven extremely effective and will provide double the service flow rates of multi-media or sand filters.

Our **95STS Single Valve Series** filters provide high quality filtered water. The system is engineered and thoroughly tested to provide years of reliable, trouble-free performance with minimal maintenance.

### For Applications Such As:

Apartments ● Boiler Treatment ● Cooling Towers ● Motels ● Schools ● Nursing Homes ● Car Wash ● Dairies ● Factories  
Laundromats ● Office Buildings ● Resorts ● Restaurants ● RO Pre-Treatment ● Hospitals

# 95STS Single Valve Series Commercial Water Filter Specifications

## Nextsand Filters

Model	Typical	RO	Max Flow To Drain	Mineral Tank		Installation		
	Service Flow Rate			Diameter	Height	Height	Depth	Width
	USGPM (L/S)	USGPM (L/S)	USGPM (L/S)	in (mm)	in (mm)	in (mm)	in (mm)	in (mm)
95STS NX14-1.5"	10 (0.63)	8 (0.50)	14 (0.88)	14 (356)	65 (1,651)	75 (1,905)	20 (508)	20 (508)
95STS NX16-1.5"	14 (0.88)	11 (0.69)	17 (1.07)	16 (406)	65 (1,651)	75 (1,905)	22 (559)	22 (559)
95STS NX18-1.5"	17 (1.071)	13 (0.819)	21 (1.32)	18 (475)	65 (1,651)	75 (1,905)	24 (610)	24 (610)



95STS Single Valve Series



**TOLL-FREE: 877-288-9888**  
**www.canaturewg-cied.com**

Regina, SK • Cambridge, ON • Whitestown, IN • Houston, TX  
 Phoenix, AZ • Guadalajara, MX