	Model	Number Of Membranes			Pump Dimensions Hp W x D x H		Connections Inlet Waste Product		Shipping Weight	
			USGPD (Liter/Day)	USGPM		Inches (mm)	Inch (mn	es	Lbs (kg)	
PREMU PRESSURE WASTE PROJUCT RECYCLE	CAN 4040-1	1	2000 (7571)	1.39 5.3	1	28x24x55 (711x610x1397)	.75 0.5 (19) (13		200 (119)	
	 [*] Membranes Nominally rated at 2000 usgpd @ 77 F. Actual prodution varies greatly incoming water tem raw water makeup, membrane type, and operating pressure General Operating Parameters Normal Operating Pressure 100-150 PSI Recommended Inlet Pressure 30 PSI Min. 65 PSI Max. Recovery Adjustable, typically 50 to 75% (dependent on feed water quality) Rejection -Typcially 98 %, (membrane dependent) Standard Features Large Blue 20" 5 Micron Cartridge Pre-Filter Multistage Booster Pump - 220 V Single Phase Low Pressure Shut Off Switch For Pump Protection Low Energy Membranes which increase production and reduces operating costs Permeate (product),Concentrate (waste) and Recycle flow meters Pre-filter, Post-filter & Membrane Pressure Gauges Automatic Inlet Shut Off Valve Unit On/ Off Switch 258 Controller Indication for Tank Full / Low Pressure /Pretreatment Lockout / Flush & Processing Optional Features 								temperature,	
CAN 4040-1 CAN4040-1XIe258TvAfTfFp230V1pSsh 91-10911001 Materials Of Construction -Frame - Epoxy Coated Carbon Steel -Pump-Goulds Multistage -Standard -Membrane Vessels: Stainless Steel -Standard -Inlet Piping - Sch 80 PVC, Brass, Stainless Steel & Braided PVC Hose -High Pressure Tubing With Brass Compression Fittings -Product Tubing NSF 51 Approved Tubing & Fittings		-Fiberglass Membrane Housings -S-100 Controller -S150 Controller -Auto Flush (INCLUDED) -TDS meter -Permeate Flush -Stainless Steel Pump -Pump Throttling Valve (INCLUDED) -Optional Membranes High Rejection Nano				- Chem f - Remote (Modbu or Ethe - Open ta	 CSA unit approval Chem feed pump plug in Remote monitoring (Modbus/TCP, BACnet/IP, or Ethernet/IP) Open tank float switch (INCLUDED) Pressure tank switch 			
		WaterGroup				CAN 4040 SERIES 1 to 6 Membranes RO UNITS				
	rGro				that may devia change previo Project	This document contains information which is proprietary to the manufacturer who reserves the right to make product revisions that may deviate from the specifications without obligation to change previous products or to note the change.ProjectDate 05/11/17 Dwg # CD-00120Rev 1				