	Model	Number Of Membranes	Rating*		Pump Hp	Dimensions W x D x H				_
			USGPD (Liter/Day)			Inches (mm)		Inches (mm)		Lbs (kg)
	CAN 2540-2	2	1200 (4542)	0.83 3.14	3/4	28x24x55 (711x610x1397)	.75 (19)	0.5 (13)	0.5 (13)	180 (82)
	 * Membranes Nominally rated at 600 usgpd Actual prodution varies greatly incoming water temperature, raw water makeup, membrane type, and operating pressure General Operating Parameters -Maximum Operating Pressure 190 PSI -Recommended Inlet Pressure 30 PSI Min. 65 PSI Max. -Recovery Adjustable, typically 50 to 75% (dependent on feed water quality) -Rejection -Typcially 98 %, (membrane dependent) Standard Features -Large Blue 20" 5 Micron Cartridge Pre-Filter -Multistage Booster Pump - 120 V Single Phase / 220v Optional -Low Pressure Shut Off Switch For Pump Protection -Low Energy Membranes which increase production and reduces operating costs -Permeate (product),Concentrate (waste) and Recycle flow meters -Pre-filter, Post-filter & Membrane Pressure Gauges -Automatic Inlet Shut Off Valve -Unit On/ Off Switch -Controller Indication for Tank Full / Low Pressure /Pretreatment Lockout / Flush & Processing 									
CAN 2540-2 Materials Of Construction		Optional Fea -Fiberglass M -S-100 Contr -Auto Flush (-TDS meter -Permeate F -Stainless St -Pump Throt -Optional Me	Aembrane H oller INCLUDEE lush eel Pump tling Valve mbranes)) (INCLUDI	ED)					
-Frame - Epoxy Coated Carbon Steel -Pump-Goulds Multistage -Standard -Membrane Vessels: Stainless Steel -Standard -Inlet Piping - Sch 80 PVC, Brass, Stainless Ste Braided PVC Hose -High Pressure Tubing With Brass Compression						1 to		SERI mbran		
-Product Tubing NSF 51 Approved Tubing & Fit					This document contains information which is proprietary to Canature. Canature reserves the right to make product revisions that may deviate from the specifications without obligation to change previous products or to note the change. Project Date 5/30/12 Re Dwg # CD-00120A 0					