

UpFlow NRV Neutralizing Filter


The UpFlow NRV Neutralizing Filter contains special media which raises the pH of acidic water and neutralizes its acidic characteristics. In addition to protecting pipes, plumbing fixtures and appliances, this filter also facilitates the oxidation of iron and manganese by raising the pH to enable an iron filter to be used. After a period of time, additional media may be required.

Features:

- Heavy duty mineral tanks with a 10 year guarantee
- Dome hole fill port on tank allows refilling of media without disconnecting plumbing.
- Designed for simple operation and service
- Upflow prevents media bed from packing/channeling



Dome hole fill port



Economical Non-Regenerating Valve (NRV) distribution head with convenient quick connect fittings

Model Description	Media Cu Ft (1)	Flow Rate USGPM (1)		Installation Space inches (mm) - W x D x H	Mineral Tank Size inches (mm)	Ship Weight Lbs (kg)
		Service	Peak			
15550948 UNF15	1.5 (42)	3 (11.4)	5 (19)	11 x 11 x 60 (279 x 279 x 1524)	10 x 54 (254 x 1372)	145 (65.8)
15550949 UNF25	2.5 (70)	6 (23)	10 (38)	14 x 14 x 60 (355 x 355 x 1524)	13 x 54 (330 x 1372)	261 (118.4)

- Maximum Water Temperature = 110°F (43°C)
- Maximum Operating Pressure = 100 PSIG (689 kPa)
- Pipe Size = 3/4"
- Peak flow rates intended for intermittent use only (10 minutes or less) and are for residential applications only. Do not use peak flow rates for commercial applications.

- At the stated service flow rates, the pressure drop through these devices will not exceed 15 psig.
- The manufacturer reserves the right to make product improvements which may deviate from the specifications and descriptions stated herein, without obligation to change previously manufactured products or to note the change.



Includes bypass valve



Your Local Plumbing Professional