

AQUA FLO®

CGAC SERIES

Granular Activated Carbon Cartridges

Aqua Flo CGAC Series Cartridges effectively reduce unwanted tastes and odors, including chlorine taste & odor from your drinking water. They are designed to allow maximum contact between the water and carbon, ensuring optimal adsorption, providing good general-purpose drinking water filtration.

FEATURES / BENEFITS:

- ◆ Effective reduction of bad taste & odor and chlorine & odor reduction
- ◆ Designed for optimal adsorption
- ◆ Post-filter to reduce carbon fines
- ◆ Available in Four Sizes: 2.5x10"; 2.5x20"; 4.5x10"; 4.5x20"
- ◆ Universal fit – Fits most standard water filter housing
- ◆ Micron – not rated

SPECIFICATIONS:

- ◆ End Caps – Polypropylene
- ◆ Gasket – SBC Rubber
- ◆ Filter Media – Granular Activated Carbon
- ◆ Outer Casing – Polypropylene
- ◆ Post Filter – Polypropylene
- ◆ Temperature Rating – 40 - 125°F (4 - 52°C)

APPLICATIONS (For water filtration only):

- ◆ Commercial/Residential Drinking Water Filtration
- ◆ Food & Beverage Filtration
- ◆ Industrial Water Filtration
- ◆ Chlorine reduction for process water



“Effectively reduce unwanted tastes and odors, including chlorine taste & odor from your drinking water.”

CGAC SERIES

Granular Activated Carbon Cartridges

SPECIFICATIONS & PERFORMANCE:

ITEM #	DESCRIPTION	DIMENSIONS	CASE QTY	SHIP WEIGHT EACH (LBS)	RATING (NOMINAL)	FLOW RATE (GPM)
26277	CGAC-10	2.5" x 10" (63.5 x 254 mm)	12	1.0	NR	1.0 US GPM (3.8 LPM)
26186	CGAC-20	2.5" x 20" (63.5 x 508 mm)	6	2.0	NR	2.0 US GPM (7.5 LPM)
26187	CGAC-10BV	4.5" x 10" (114.3 x 254 mm)	8	1.9	NR	2.0 US GPM (7.5 LPM)
26188	CGAC-20BV	4.5" x 20" (114.3 x 508 mm)	4	3.8	NR	4.0 US GPM (15.1 LPM)

WARNING: Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system.

NOTE: Initial flow pressure drop less than 5 psi at rated flow rate. Change filter when pressure drop exceeds 10 psi.

AQUA FLO®

A Division of



Your Local Water Specialist