NOVO®
PROFESSIONAL WATER SYSTEMS

NVO489UF Cabinet SPECIFICATION SHEET

7 yr WARRANTY
CONTROL VALVE

LIFETIME WARRANTY
PRESSURE TANK



Water Softener

1" Porting, High-Efficiency, Compact Size

The 489UF cabinet softener offers high-efficiency, high-flow water softening in a compact, space-saving design. Third-party certified to provide luxuriously soft water, enjoy advanced features while using less salt and water.

KEY FEATURES

Upflow Regeneration: Saves salt by preserving the unused portion of the softening bed from unnecessary ion exchange.

Precision Brining: Calculates the exact amount of brine required to regenerate, using up to 30% less salt.

Automatic System Refresh: If no water is used for seven (7) days, the system will perform an automatic refresh to prevent bacteria growth.

Backwash Frequency Preset: Save up to 2,000 gallons of water per year by skipping up to ten (10) backwash cycles on clean municipal water supply.

Soft Water Brine Tank Refill: Keeps tank & injectors clean.

Soft Water Recharge: If capacity goes below 3%, an automatic 15-minute recharge restores softening until the next regeneration.

Cabinet Features: Cabinet comes with safety float and air check.

VALVE FEATURES

True 1" Porting For high-flow applications.

1" 90-Degree Elbows Included for easy installation.

Timesaving Quick Connect Fittings. Bypass included Quick connect fittings on bypass, drain line (10' included), brine line and power cord.

Four Line Touch Pad LCD Display No-touch rotating information display. Just set the time, date, and hardness.

48-Hour Programming Memory Automatic programming restore for up to 48 hours during power loss.



USES UP TO 75% LESS SALT & 64% LESS WATER

LEAD FREE UPC C ®
IAPMO R&T Certified to NSF/ANSI 44, 372 and CSA B483.1.

NSF COMPONENT

Technical Specifications

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	NVO489UF-100C
Item Number	15020693
CAPACITY (GRAINS)	
@ 12 lbs/Cubic Feet	30,000
@ 6 lbs/Cubic Feet Factory Setting	**25,000**
@ 3 lbs/Cubic Feet	15,000
REGENERATION WATER USAGE (GALLONS)	
Clean Water (Factory Setting)	48.6 gal
Problem Water	69.5 gal
Resin Quantity (Cubic Feet)	1.0 ft^3
Media Loaded	Yes
Salt Storage Capacity	225 lbs
Flow Rate @ 15 psi Pressure Drop	12.0 gpm
Flow Rate @ 25 psi Pressure Drop	16.0 gpm
Back Wash Flow Rate	2.5 US gpm
Shipping Weight	110 lbs
Regeneration Type	UPFLOW (COUNTER CURRENT)
Plumbing Connections	INCLUDES 1" 90° NPT ELBOWS
Resin Type	AQUAFINE® 8% CATION EXCHANGE RESIN
Electrical Requirements	INPUT 120V 60 Hz - OUTPUT 12V 650mA
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)

DIMENSIONS

NVO489UF-100C

13.8" X 23.6" X 43.3





Salt Storage Large, easy to fill cabinet.

QUICK LINKS

- Homeowner's Manual
- Installation Guide
- Maintenance Guide
- Trouble Shooting Guide
- Parts Breakdown
- Programming Guide
- Warranty Sheet

NOVO® PROFESSIONAL WATER SYSTEMS | A Division of Canature WaterGroup | MEMBER Water Quality Association | CWQA | CIPH Canadian Institute of Plumbing & Heating | PHCC PLUMBING-HEATING-COOLING CONTRACTORS ASSOCIATION Best People. Best Practices.

Toll Free: 877-288-9888 | **www.novowater.com** | Regina, SK • Cambridge, ON • Whitestown, IN • Houston, TX • Phoenix, AZ • Guadalajara, MX

DESIGNED, ENGINEERED & ASSEMBLED IN NORTH AMERICA

80155778 REV 3 2026-07-15 Download only