

### Water Softener

**Reliable, Affordable, Compact Size**

The Econo Flo cabinet softener is perfect for homeowners looking for a reliable water softener that saves space. Third-party certified to provide soft water throughout the home, the Econo Flo is known for its long-lasting performance.

#### KEY FEATURES

**OUTSTANDING VALUE:** Simple electronics for the same price as mechanical metered units.

**ESSENTIAL FEATURES:** Adjustable cycle times and optional regeneration modes (meter immediate, meter delayed, meter override, calendar clock modes).

**RELIABLE PERFORMANCE:** 5-year control valve and 10-year pressure tank warranty.

**CABINET FEATURES:** Cabinet comes with safety float and air check.

#### VALVE FEATURES

##### 3/4" 90-DEGREE ELBOWS

Included for easy installation.

##### SIMPLE ELECTRONICS

Just set time of day, hardness and number of people.

##### OPTIONAL REGENERATION MODES

Meter immediate, meter delayed, meter override, calendar clock modes.

##### 48-HOUR PROGRAMMING MEMORY

Automatic programming restore for up to 48 hours during power loss.

##### TIMESAVING QUICK CONNECT FITTINGS & PRE-INSTALLED BYPASS

Quick connect fittings on bypass, drain line (10' included), brine line and power cord, for easier, faster installations.



COMPONENT



CONTROL VALVE



PRESSURE TANK



**USES UP TO 50%  
LESS SALT & 28%  
LESS WATER**



IAPMO R&T Certified to  
NSF/ANSI 44, 372 and  
CSA B483.1.

# Technical Specifications

## QUICK LINKS



Homeowner's  
Manual



Installation Guide



Maintenance  
Guide



Trouble Shooting  
Guide



Parts Breakdown



Programming Guide



Warranty Sheet

## PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	EFC-100
Item Number	82118
CAPACITY (GRAINS)	
@ 10 lbs/Cubic Feet	26,500
@ 6 lbs/Cubic Feet Factory Setting	<b>22,000</b>
@ 3 lbs/Cubic Feet	14,000
Service Flow Rate	10.0 US gpm
Backwash Flow Rate	2.4 US gpm
Total Resin (Cubic Feet)	1.0 ft <sup>3</sup>
Salt Storage Capacity	225 lbs
Shipping Weight	110 lbs
Regeneration Type	DOWNFLOW (COCURRENT)
Plumbing Connections	INCLUDES 3/4" 90° NPT ELBOWS
Resin Type	AQUAFINE® 8% CATION EXCHANGE RESIN
Electrical Requirements	INPUT 120V 60 Hz - OUTPUT 12V 650mA
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)

## DIMENSIONS

EFC-100
13.8" X 23.6" X 34.5"



WaterGroup®  
Professional Treatment Solutions

A DIVISION OF  
Canature  
WaterGroup

Water  
Quality  
Association

CWQA  
Canadian Water Quality Association

CPHA  
Canadian Institute  
of Plumbing & Heating

PHCC  
PLUMBING-HEATING-COOLING  
CONTRACTORS ASSOCIATION  
Best People. Best Practices.

Toll Free: 877-288-9888 | [www.watergroup.com](http://www.watergroup.com) | Regina, SK • Cambridge, ON • Whitestown, IN • Houston, TX • Phoenix, AZ • Guadalajara, MX

DESIGNED, ENGINEERED & ASSEMBLED IN NORTH AMERICA

80155813 REV 1 2025-04-08 Download only