

Water Softener & Carbon Filter with WiFi

High-Flow, WiFi Monitoring, Reduces Bad Taste & Odor

The ideal solution for large households on municipal water, the 189UFHTO with Aqua Alert® combines high-efficiency, high-flow water softening with whole home carbon filtration and the ability to control your system from your phone. Third-party certified to provide soft water and reduce bad taste and odor caused by chlorine and chloramines.

KEY FEATURES

AQUA ALERT®: Enjoy full control from the convenience of your phone with smart features like reminders to add salt, and real-time salt and water tracking. Optional leak alarm and remote water shut off give you complete control and peace of mind.

WHOLE HOME CHLORINE REDUCTION: IAPMO certified for chlorine reduction. AquaFine® catalytic carbon reduces chlorine, chloramines and chlorine by-products such as chloroform and other trihalo-methanes (THMs).

UPFLOW REGENERATION: Saves salt by preserving the unused portion of the softening bed from unnecessary ion exchange.

PRECISION BRINING: Calculates the exact amount of brine required to regenerate, using up to 30% less salt.

AUTOMATIC SYSTEM REFRESH: If no water is used for seven (7) days, the system will perform an automatic refresh to prevent bacteria growth.

SOFT WATER BRINE TANK REFILL: Keeps tank & injectors clean.

SOFT WATER RECHARGE: If capacity goes below 3%, an automatic 15-minute recharge restores softening until the next regeneration.

TANK FEATURES: Brine tank with safety float, air check and injection molded brine grid to reduce bridging. Moisture wicking neoprene tank jacket included on all pressure tanks.

VALVE FEATURES

TRUE 1" PORTING

For high-flow applications.

1" 90-DEGREE ELBOWS

Included for easy installation.

TIMESAIVING QUICK CONNECT FITTINGS & PRE-INSTALLED BYPASS

Quick connect fittings on bypass, drain line (10' included), brine line and power cord.

TANKMATE™ Unique design sends water through both the carbon and resin tanks in a single pass.

OPTIONAL LEAK ALARM

A physical leak alarm placed near the floor drain will sound if a leak is detected. A Leak Alarm message will be sent to your e-mail.

AQUA ALERT® SALT SENSOR

Ensures your system never runs out of salt.

FOUR LINE TOUCH PAD LCD DISPLAY

No-touch rotating information display. Just set the time, date, and hardness.

AQUA ALERT® ENABLED

Ensures your system is performing properly with e-mail notifications.

48-HOUR PROGRAMMING MEMORY

Automatic programming restore for up to 48 hours during power loss.



CONTROL VALVE



PRESSURE TANK



AQUA ALERT®

*Based on model: WG189UFHTO-150.

97% CHLORINE REMOVAL FOR OVER 1,100,000 GALLONS*



IAPMO R&T Certified to NSF/ANSI 44, 372 and CSA B483.1.



IAPMO R&T Certified to NSF/ANSI 372 and 42 for Chlorine Reduction

Technical Specifications

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	WG189UFHTO-100 WF	WG189UFHTO-150 WF	WG189UFHTO-200 WF	WG189UFHTO-300 WF
Item Number	82420-1	82421-1	82422-1	82423-1
Salt Used Per Regeneration	6.0 lbs	9.0 lbs	12.0 lbs	18.0 lbs
Water Used Per Regeneration	86.4 gal	148.0 gal	162.4 gal	224.8 gal
Hardness Removal (Grains)	21,600	32,400	43,200	64,800
Tank #1 Carbon Quantity (Cubic Feet)	1.0 ft ³	1.50 ft ³	2.0 ft ³	3.0 ft ³
Tank #2 Resin Quantity (Cubic Feet)	1.0 ft ³	1.50 ft ³	2.0 ft ³	3.0 ft ³
Pressure Tank Size (inches)	9 x 48	10 x 54	12 x 52	14 x 65
Media Loaded	Yes	Yes	Yes	No
Salt Storage Capacity	270 lbs	270 lbs	350 lbs	420 lbs
Flow Rate @ 15 psi Pressure Drop	7.2 US gpm	7.4 US gpm	9.0 US gpm	9.2 US gpm
Flow Rate @ 25 psi Pressure Drop	10.0 US gpm	10.1 US gpm	11.9 US gpm	12.1 US gpm
Backwash Flow Rate	5.0 US gpm	5.0 US gpm	7.0 US gpm	10.0 US gpm
Shipping Weight	167 lbs	218 lbs	278 lbs	425 lbs
Regeneration Type	UPFLOW (COUNTER CURRENT)			
Plumbing Connections	INCLUDES 1" 90° NPT ELBOWS			
Resin Type	AQUAFINE® 8% CATION EXCHANGE RESIN			
Carbon Type	AQUAFINE® CATALYTIC CARBON			
Electrical Requirements	INPUT 120V 60 Hz - OUTPUT 12V 650mA			
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)			
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)			

DIMENSIONS

WG 189UFHTO WF	100	150	200	300
TANK/VALVE A x B (inches)	60 x 23	66 x 24	64 x 26	78 x 34
BRINE TANK C x D (inches)	18.1 x 34.5	18.1 x 34.5	20.3 x 37.4	23.0 x 40.5

AQUA ALERT® WIFI Optional Accessories	
ITEM NUMBER	DESCRIPTION
60010380	KIT, LEAK SENSOR & 1" ELECTRIC BALL VALVE
60010378	LEAK SENSOR, WIFI
60010379	1" ELECTRIC BALL VALVE, WIFI



QUICK LINKS



Homeowner's Manual



Installation Guide



Maintenance Guide



Trouble Shooting Guide



Parts Breakdown



Programming Guide



Warranty Sheet



Aqua Alert Manual