

Water Softener

1" Porting, High-Efficiency, Compact Size

The 189UF cabinet softener offers high-efficiency, high-flow water softening in a compact, space-saving design. Third-party certified to provide luxuriously soft water, enjoy advanced features while using less salt and water

KEY FEATURES

UPFLOW REGENERATION: Saves salt by preserving the unused portion of the softening bed from unnecessary ion exchange.

PRECISION BRINING: Calculates the exact amount of brine required to regenerate, using up to 30% less salt.

AUTOMATIC SYSTEM REFRESH: If no water is used for seven (7) days, the system will perform an automatic refresh to prevent bacteria growth.

BACKWASH FREQUENCY PRESET: Save up to 2,000 gallons of water per year by skipping up to ten (10) backwash cycles on clean municipal water supply.

SOFT WATER BRINE TANK REFILL: Keeps tank & injectors clean.

SOFT WATER RECHARGE: If capacity goes below 3%, an automatic 15-minute recharge restores softening until the next regeneration.

CABINET FEATURES: Cabinet comes with safety float and air check.

VALVE FEATURES

TRUE 1" PORTING

For high-flow applications.

1" 90-DEGREE ELBOWS

Included for easy installation.

TIMESAIVING QUICK CONNECT FITTINGS & PRE-INSTALLED BYPASS

Quick connect fittings on bypass, drain line (10' included), brine line and power cord.

UNIQUE BYPASS DESIGN

Integrated turbine meter saves space, eliminates connections and is more durable.

FOUR LINE TOUCH PAD LCD DISPLAY

No-touch rotating information display. Just set the time, date, and hardness.

48-HOUR PROGRAMMING MEMORY

Automatic programming restore for up to 48 hours during power loss.



CONTROL VALVE



PRESSURE TANK



**USES UP TO
75% LESS SALT
& 64% LESS WATER**



IAPMO R&T Certified to NSF/ANSI 44, 372 and CSA B483.1.



COMPONENT

Technical Specifications

QUICK LINKS



Homeowner's Manual



Installation Guide



Maintenance Guide



Trouble Shooting Guide



Parts Breakdown



Programming Guide



Warranty Sheet

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	WG189UF-100C
Item Number	82285
CAPACITY (GRAINS)	
@ 10 lbs/Cubic Feet	30,000
@ 6 lbs/Cubic Feet Factory Setting	25,000
@ 3 lbs/Cubic Feet	15,000
REGENERATION WATER USAGE (GALLONS)	
Clean Water (Factory Setting)	48.6 gal
Problem Water	69.5 gal
Resin Quantity (Cubic Feet)	1.0 ft ³
Media Loaded	Yes
Salt Storage Capacity	225 lbs
Flow Rate @ 15 psi Pressure Drop	12.0 US gpm
Flow Rate @ 25 psi Pressure Drop	16.0 US gpm
Back Wash Flow Rate	2.5 US gpm
Shipping Weight	110 lbs
Regeneration Type	UPFLOW (COUNTER CURRENT)
Plumbing Connections	INCLUDES 1" 90° NPT ELBOWS
Resin Type	AQUAFINE® 8% CATION EXCHANGE RESIN
Electrical Requirements	INPUT 120V 60 Hz - OUTPUT 12V 650mA
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)

DIMENSIONS



WaterGroup®
Professional Treatment Solutions

A DIVISION OF
Canature
WaterGroup

Water
Quality
Association

CWQA
Canadian Water Quality Association

Canadian Institute
of Plumbing & Heating

PHCC
PLUMBING-HEATING-COOLING
CONTRACTORS ASSOCIATION
Best People. Best Practices.

Toll Free: 877-288-9888 | www.watergroup.com | Regina, SK • Cambridge, ON • Whitestown, IN • Houston, TX • Phoenix, AZ • Guadalajara, MX

DESIGNED, ENGINEERED & ASSEMBLED IN NORTH AMERICA

80155819 2025-04-11 Download only