

Water Filter

Non-Regenerating, Whole-Home Carbon Filter, Reduces Chlorine and Bad Taste & Odors

Once water arrives safely at your home there is no further need for disinfectants. In fact, they are undesirable. Disinfectants can create unpleasant tastes and odors, dry out skin, damage plumbing, and generate potentially harmful by-products. The NRVTO and NRVTOK whole-home carbon filters reduce unwanted chlorine from water throughout the home.

KEY FEATURES

AFFORDABLE: Economical whole-house carbon filtration solution for reducing chlorine and other bad tastes and odors. TOK models reduce chlorine plus hydrogen sulfide (H₂S) caused by sulphate reducing bacteria common in warmer climates.

CERTIFIED CHLORINE REDUCTION: Certified by IAPMO R&T to NSF/ANSI 42 for Chlorine Reduction (based on the NRVTO-150 model).

GRANULAR ACTIVATED COCONUT SHELL CARBON: AQUAFINE® is a high activity granular activated carbon manufactured by steam activation from select coconut shell charcoal. Its large micropore volume makes it particularly well-suited for the reduction of chlorinated by-products such as chloroform and other trihalomethanes (THMs). An important feature of this material is its superior mechanical hardness and the extensive dedusting during its manufacture ensures an exceptionally clean activated carbon product.

VALVE FEATURES

FACTORY INSTALLED ONE-PIECE BYPASS

NON-REGENERATING VALVE

Economical non-backwashing distribution head with convenient quick connect fittings.

3/4" 90-DEGREE ELBOWS

Included for each installation.




DISTRIBUTION HEAD



PRESSURE TANK

*Based on model: NRVTO-150.

97% CHLORINE REMOVAL FOR OVER 1,100,000 GALLONS*



Certified by IAPMO R&T to NSF/ANSI 372 and 42 for Chlorine Reduction

Technical Specifications

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

MODEL NUMBER	NRV TO-100	NRV TO-150	NRV TOK-100	NRV TOK-150
Item Number	15054073	15054074	15054075	15054076
Peak Flow Rates	4.0 gpm	5.0 gpm	4.0 gpm	5.0 gpm
Filter Media Volume (Cubic Feet)	1.0 ft ³	1.5 ft ³	1.0 ft ³	1.5 ft ³
Filter Tank Size	9 x 48	10 x 54	9 x 48	10 x 54
Media Type	TO MODELS: AQUAFINE® GRANUAL ACTIVATED COCONUT CARBON TOK MODELS: AQUAFINE® GRANUAL ACTIVATED COCONUT CARBON WITH KDF DISTRIBUTOR			
Media Loaded	Yes	Yes	Yes	Yes
KDF Protector	No	No	Yes	Yes
Tank Jacket	No	No	No	No
Shipping Weight	53 lbs	72 lbs	60 lbs	72 lbs
Plumbing Connections	INCLUDES 3/4" 90° NPT ELBOWS. BYPASS INCLUDED.			
Electrical Requirements	NONE			
Water Temperature Limits	MIN 40° - MAX 110° F (4° - 43° C)			
Water Pressure Limits	MIN 30 - MAX 125 PSI (207 - 862 KPA)			

QUICK LINKS



Homeowner's Manual



Installation Guide



Maintenance Guide



Trouble Shooting Guide



Parts Breakdown



Programming Guide



Warranty Sheet

DIMENSIONS

NRVTO & NRVTOK Filters	100	150
TANK/VALVE A x B (inches)	52 x 9	58 x 10

