

# Designer RO Faucets

Designer RO Faucets are a stylish addition to any kitchen. The NSF Certified lead-free ceramic disk faucets are available in many attractive finishes to coordinate with any decor. The faucets feature lead-free plastic water passages and lead-free brass gooseneck spouts that swivel 360 degrees for ease of use.



VS905

VS888



#### NON AIR GAP FAUCETS

PART #	DESCRIPTION
87613	Faucet, VS888, Matte Black
87588	Faucet, VS888, Antique Brass
87581	Faucet, VS888, Brushed Nickel
87580	Faucet, VS888, Polished Chrome
87584	Faucet, VS888, Black
87583	Faucet, VS905, Brushed Nickel
87587	Faucet, VS905, Oil Rubbed Bronze
87582	Faucet, VS905, Polished Chrome
87591	Faucet Colour Sample Display
92710	Stand, Display

#### AIR GAP, NSF / ANSI 61 CERTIFIED

PART #	DESCRIPTION
92653	Faucet, VS888, Polished Chrome, Air Gap
87597	Faucet, VS888, Brushed Nickel, Air Gap
87592	Faucet, VS905, Polished Chrome, Air Gap
87596	Faucet, VS905, Antique Bronze, Air Gap
87594	Faucet, VS905, Brushed Nickel, Air Gap

Specifications	VS888	VS905
Height	11.5" (292mm)	11.075" (281.32mm)
Spout Reach	5.7" (146mm)	4.75" (120mm)
Mounting Hole Diameter	1/2" (12.5mm)	1/2" (12.5mm)
Base Diameter	1.73" (44mm)	1.76" (44.8mm)
Connection	1/4" compression nut fitting	1/4" compression nut fitting
Operating Pressure	125 PSI/8.3BAR	125 PSI/8.3BAR
Flow Rate	1.0 gpm/3.785lpm @35 PSI/2.32BAR	1.0 gpm/3.785lpm @35 PSI/2.32BAR
Temp Rating	4°C/40°F to 70°C/158°F	4°C/40°F to 70°C/158°F
Warranty	2 Years	2 Years

\* All mounting hardware included. A 3/8" quick connect faucet adapter fitting (#PP3212U7W) can be purchased separately.