



CONTROL
VALVE



PRESSURE
TANK

Water Softener & Whole Home Carbon Filter

High-Flow, High-Efficiency, Reduces Bad Taste & Odor

Ideal for households on municipal water, the 485UFHTO combines high-efficiency, high-flow water softening with whole home carbon filtration. Third-party certified to provide soft water while reducing bad taste and odor caused by chlorine and chloramines.

KEY FEATURES

Whole Home Chlorine Reduction: IAPMO certified for chlorine reduction. AquaFine[®] catalytic carbon reduces chlorine, chloramines and chlorine by-products such as chloroform and other trihalomethanes (THMs).

Upflow Regeneration: Saves salt by preserving the unused portion of the softening bed from unnecessary ion exchange.

Precision Brining: Calculates the exact amount of brine required to regenerate, using up to 30% less salt.

Automatic System Refresh: If no water is used for seven (7) days, the system will perform an automatic refresh to prevent bacteria growth.

Soft Water Brine Tank Refill: Keeps tank & injectors clean.

Soft Water Recharge: If capacity goes below 3%, an automatic 15-minute recharge restores softening until the next regeneration.

Tank Features: Brine tank with safety float, air check and injection molded brine grid to reduce bridging. Moisture wicking neoprene tank jacket included on all pressure tanks.

VALVE FEATURES

Unique Bypass Design
Integrated turbine meter saves space, eliminates connections and is more durable.

Timesaving Quick Connect Fittings & Pre-Installed Bypass
Quick connect fittings on bypass, drain line (10' included), brine line and power cord.

Backlit LCD Display
"No Touch" display rotates key information including last regeneration date and volume remaining.

User-Friendly Programming
Just set the time, date, number of people and hardness.

48-Hour Programming Memory
Automatic programming restore for up to 48 hours during power loss.

TankMate[®] Unique design sends water through both the carbon and resin tanks in a single pass.



**97% CHLORINE
REMOVAL FOR OVER
1,100,000 GALLONS***

*Based on model: NVO485UFHTO-150.



**IAPMO R&T Certified to
NSF/ANSI 44, 372 and
CSA B483.1.**



**IAPMO R&T Certified to
NSF/ANSI 372 and 42 for
Chlorine Reduction**

Technical Specifications

PROFESSIONALLY ENGINEERED FOR PERFORMANCE

| MODEL NUMBER | NVO485UFHTO-100 | NVO485UFHTO-150 | NVO485UFHTO-200 | NVO485UFHTO-300 |
|--------------------------------------|------------------------------------------------------------------------------------------------|----------------------|---------------------|---------------------------------------|
| Item Number | 15020484-1 | 15020485-1 | 15020486-1 | 15020487-1 |
| MODEL NUMBER | NVO485UFHTOK-100 | NVO485UFHTOK-150 | NVO485UFHTOK-200 | TOK models available in the USA only. |
| Item Number | 15024069-1 | 15024070-1 | 15024071-1 | |
| Salt Used Per Regeneration | 6.0 lbs | 9.0 lbs | 12.0 lbs | 18.0 lbs |
| Water Used Per Regeneration | 86.4 gal | 148.0 gal | 162.4 gal | 224.8 gal |
| Hardness Removal (Grains) | 25,000 | 37,500 | 50,000 | 75,000 |
| Tank #1 Carbon Quantity (Cubic Feet) | 1.0 ft ³ | 1.50 ft ³ | 2.0 ft ³ | 3.0 ft ³ |
| Tank #2 Resin Quantity (Cubic Feet) | 1.0 ft ³ | 1.50 ft ³ | 2.0 ft ³ | 3.0 ft ³ |
| Pressure Tank Size (Inches) | 9 x 48 | 10 x 54 | 12 x 52 | 14 x 65 |
| Media Loaded | Yes | Yes | Yes | No |
| Salt Storage Capacity | 270 lbs | 270 lbs | 350 lbs | 420 lbs |
| Flow Rate @ 15 psi Pressure Drop | 7.2 US gpm | 7.4 US gpm | 9.0 US gpm | 9.2 US gpm |
| Flow Rate @ 25 psi Pressure Drop | 10.0 US gpm | 10.1 US gpm | 11.9 US gpm | 12.1 US gpm |
| Backwash Flow Rate | 4.0 US gpm | 5.0 US gpm | 7.0 US gpm | 11.0 US gpm |
| Shipping Weight | 167 lbs | 218 lbs | 278 lbs | 425 lbs |
| Regeneration Type | UPFLOW (COUNTER CURRENT) | | | |
| Plumbing Connections | INCLUDES 3/4" 90° NPT ELBOWS | | | |
| Resin Type | AQUAFINE® 8% CATION EXCHANGE RESIN | | | |
| Carbon Type | HTO MODELS - AQUAFINE® CATALYTIC CARBON HTOK MODELS - AQUAFINE® CATALYTIC CARBON WITH KDF85 | | | |
| Electrical Requirements | INPUT 120V 60 Hz - OUTPUT 12V 650mA | | | |
| Water Temperature Limits | MIN 40° - MAX 110° F (4° - 43° C) | | | |
| Water Pressure Limits | MIN 30 - MAX 125 PSI (207 - 862 KPA) | | | |

DIMENSIONS

| NVO 489UFHTO | 100 | 150 | 200 | 300 |
|------------------------------|---------------|--------------|--------------|--------------|
| TANK/VALVE A x B (inches) | 56.25 x 22.75 | 62.5 x 23.25 | 60.75 x 24.5 | 74.5 x 33.25 |
| BRINE TANK C x D (inches) | 18.1 x 34.7 | 18.1 x 34.7 | 20.3 x 37.4 | 23.0 x 40.5 |



QUICK LINKS



Homeowner's Manual



Installation Guide



Maintenance Guide



Trouble Shooting Guide



Parts Breakdown



Programming Guide



Warranty Sheet

