VicBooth Office



The VicBooth Office is a complete sustainable ecosystem of phone booths, private spaces, and isolated meeting rooms for the future office.

The VicBooth Office system is flexible, future-proof, and can adapt to changes in the office environment. Vicoustic developed modular booths in different sizes, with a wide range of accessories that can be upgraded and split into smaller units.

Dimensions

Configuration	Exterior	Interior
1×1	1076 × 1030 × 2277 mm	968 × 968 × 2008 mm
1×2	1076 × 2030 × 2277 mm	968 × 1968 × 2008 mm
1×3	1076 × 3030 × 2277 mm	968 × 1968 × 2008 mm
2×2	2076 × 2030 × 2277 mm	1968 × 1968 × 2008 mm
2×3	2076 × 3030 × 2277 mm	1968 × 2968 × 2008 mm
3×3	3076 × 3030 × 2277 mm	2968 × 2968 × 2008 mm
3×4	3076 × 4030 × 2277 mm	2968 × 3968 × 2008 mm

Packaging Info

Configuration	Dimensions	Total Boxes	Weight*
1×1	(1×)2120×255×190+(2×)1100×1100×160 +(4×)2210×1000×100+(1×)530×205×120	7	214 Kg
1×2	(2×)2120×255×190+(4×)1100×1100×160 +(6×)2210×1000×100+(1×)530×205×120	13	TBA
1×3	(3×)2120×255×190+(6×)1100×1100×160 +(8×)2210×1000×100+(2×)530×205×120	19	353 Kg
2×2	(3×)2120×255×190+(8×)1100×1100×160 +(8×)2210×1000×100+(2×)530×205×120	21	523 Kg
2×3	(4×)2120×255×190+(12×)1100×1100×160 +(10×)2210×1000×100+(2×)530×205×120	26	773 Kg
3×3	(5×)2120×255×190+(18×)1100×1100×160 +(12×)2210×1000×100+(3×)530×205×120	38	TBA
3×4	(6×)2120×255×190+(24×)1100×1100×160 +(14×)2210×1000×100+(4×)530×205×120	48	TBA

* Average weight, depends on the chosen walls and doors.

Speech Level Reduction Measurements

According to the values obtained for the Speech Level Reduction parameter (DS,A) and the criteria provided by the international standard, it is possible to conclude that the VicBooth Office is a Class B enclosure, meaning that according to the referred standard it "produces acceptable speech privacy if the background noise level of the room is at least 35 dB LAeq". Therefore, it is possible to conclude that VicBooth Office can provide acceptable speech privacy in any of the modern office spaces.

Materials

Structure: MDF.HLS Walls: MDF with Melamine finish; VMT interior made with VicPET Wool Exterior door handle: Coated steel Interior door handle: Leather Door Window and Window: Laminated glass

Floor: Needled pile carpet (Dark Grey)

Finishes



More info

Cable Passage: Ø 70 mm



Allows you to run cables even after the booth is assembled.

Passive Ventilation: Airflow labyrinth



Allows you to run cables even after the booth is assembled.

Silent Mechanical Ventilation

Includes a mechanical ventilation system to be attached to the ceiling, ensuring a total **air renovation of a single unit in less than 2 minutes**, with a very low noise within the booth (NR21).