


6" Round Trim LED Recessed Lights




A.



4 1/7" (L) X 3 1/2" (W)
ENGINE FOR CRLC4




B.



4 1/7" (L) X 5" (W)
ENGINE FOR CRLC4




C.



2 3/4" (H) X 4 1/4" (W) X 6 1/3" (D)
SQUARE & OPEN RECESSED TRIM



D.



2 3/4" (H) X 4 1/4" (W) X 6 1/3" (D)
SQUARE & OPEN RECESSED TRIM

Wattage

10W / 15W / 20W / 27W / 34W / 40W

Voltage Input

120-277VAC
50/60Hz

Efficacy

80-86 LPW




Dimming

0-10V Dimmable

Finish

6" Haze & White Finish Trim
Recessed Mounting

Color Temperatures

 3000K  4000K  5000K

Features



Catalog No.	Fig.	Catalog No.	Fig.
CRLC-EGN-15W-30K-D	A.	CRLC6-15W-MCT-A-D	C.
CRLC-EGN-15W-40K-D	A.	CRLC6-15W-MCT-A-D-WH	D.
CRLC-EGN-15W-50K-D	A.	CRLC6-20W-MCT-A-D	C.
CRLC-EGN-15W-MCT-D	A.	CRLC6-20W-MCT-A-D-WH	D.
CRLC-EGN-20W-50K-D	A.	CRLC6-20W-MCTP-A-D	C.
CRLC-EGN-20W-MCT-D	A.	CRLC6-20W-MCTP-A-D-WH	D.
CRLC-EGN-20W-MCTP-D	A.	CRLC6-40W-MCTP-A-D	C.
CRLC-EGN-40W-MCTP-D	B.	CRLC6-40W-MCTP-A-D-WH	D.

Factory-Installed Options

Watts	EM Options	Description	Photocell	Description	Paint	Sensor	Description
CRLC	OPT-EM-HB1EXT	EXTERNAL	N/A	N/A	N/A	N/A	N/A