


LMW



Optional Posts
see page A38



- | OPTIONS | |
|----------------|--|
| PHOTOCELL | |
| MOTION SENSOR | |
| BATTERY BACKUP | |

TECHNICAL SPECIFICATIONS:

- :: Die-cast aluminum with powder coat finish
- :: Lumileds Lexeon 3030 high flux LED
- :: High transparent tempered glass
- :: Voltage: 120-277V
- :: Beam Angle: 110° X 100°
- :: CRI: >80
- :: Power Factor: 90%
- :: Operating Temp: -4°F to 68°F
- :: 70,000 hour rated life
- :: 7-year warranty
- :: Suitable for Wet Locations, IP54

APPLICATIONS:

- :: Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas, residential areas, balcony, terrace, small shops.



LED MINI CUTOFF WALL PACKS

CATALOG NO.		WATTS	LUMENS	COLOR TEMP	DIMENSIONS
BRONZE	WHITE				
LMW-12W-30K	LMW-12W-30K-WH	12W	1300LM	3000K	5-1/8"(H) x 5"(W) x 23/4"(L)
LMW-12W-40K	LMW-12W-40K-WH	12W	1300LM	4000K	
LMW-12W-50K	LMW-12W-50K-WH	12W	1300LM	5000K	