


**LWA**



**TECHNICAL SPECIFICATIONS:**

- :: 0~90° Adjustable Cutoff Wall Packs locks into position
- :: Die-cast aluminum with powder coat finish
- :: Lumileds Lexeon 3030 high flux LED
- :: Polycarbonate Optic Lens
- :: Voltage: 120-277V
- :: CRI: >80
- :: Beam Angle: 100°X80°
- :: Power Factor: 95%
- :: Operating Temp: -4°F to 104°F
- :: 70,000 hour rated life
- :: 7-year warranty
- :: Suitable for Wet Locations, IP54



12W, 20W, 30W, 50W  
in white  
Quick Ship Available

- OPTIONS**
- PHOTOCELL
  - MOTION SENSOR
  - BATTERY BACKUP
  - FIXTURE COLOR

**APPLICATIONS:**


- :: Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas.
- :: Replace existing HID flood lights/ wall packs
- :: Great for use with motion sensors or other instant on/off controls



Optional Posts for LWA-12W  
see page A38



Shown with Optional Shroud  
See Page A27



(80W & 120W only)

**LED CUTOFF & ADJUSTABLE WALL PACKS**

CATALOG NO.		WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE	DIMENSIONS
BRONZE	WHITE					
LWA-12WW	LWA-12WW-WH	12W	1100LM	3000K	50~70 MH	5" (W) x 6" (H) x 4" (D)
LWA-12NW	-	12W	1200LM	4000K	50~70 MH	
LWA-12CW	LWA-12CW-WH	12W	1200LM	5000K	50~70 MH	
LWA-20WW	LWA-20WW-WH	20W	2000LM	3000K	70~100 MH	8" (W) x 9" (H) x 4.5" (D)
LWA-20NW	-	20W	2200LM	4000K	70~100 MH	
LWA-20CW	LWA-20CW-WH	20W	2200LM	5000K	70~100 MH	
LWA-30WW	LWA-30WW-WH	30W	3000LM	3000K	100~125 MH	11" (W) x 13" (H) x 6" (D)
LWA-30NW	-	30W	3200LM	4000K	100~125 MH	
LWA-30CW	LWA-30CW-WH	30W	3200LM	5000K	100~125 MH	
LWA-50WW	LWA-50WW-WH	50W	4900LM	3000K	150~200 MH	11" (W) x 13" (H) x 6" (D)
LWA-50NW	-	50W	5200LM	4000K	150~200 MH	
LWA-50CW	LWA-50CW-WH	50W	5200LM	5000K	150~200 MH	
LWA-80WW	-	80W	8800LM	3000K	200~300 MH	11" (W) x 13" (H) x 6" (D)
LWA-80NW	-	80W	9000LM	4000K	200~300 MH	
LWA-80CW	-	80W	9000LM	5000K	200~300 MH	
LWA-120WW	-	120W	13700LM	3000K	300~400 MH	11" (W) x 13" (H) x 6" (D)
LWA-120NW	-	120W	13700LM	4000K	300~400 MH	
LWA-120CW	-	120W	13700LM	5000K	300~400 MH	