



TECHNICAL SPECIFICATIONS:

- :: Multi CCT (Selectable Switch on the Back of the driver)
- :: Dimmable down to 10% using a standard TRIAC LED dimmer (refer to website for more information)
- :: LED: Epistar chip (COB)
- :: Construction: Spun aluminum with white powder coat finish
- :: Optics: White translucent acrylic lens
- :: CRI: 90+
- :: Power Factor: 90%
- :: Operating temperature: 104°F
- :: Rated life: 50,000 hrs
- :: Suitable for wet locations (Except 3")
- :: 5-year warranty

APPLICATIONS:

:: LED retrofit trim have been designed to be a flexible lighting solution for retrofit and new construction applications, Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications


























LED DOWNLIGHTS (SMOOTH TRIM)—ROUND

CATALOG	WATTS	COLOR TEMP	LPW	DIAMETER
RDL3-MCT-MCT5	7W	2700K/3000K/3500K/4000K/5000K	80LM/W	3"
RDL4-MCT-MCT5	8W	2700K/3000K/3500K/4000K/5000K	81LM/W	4"
RDL6-MCT-MCT5	14W	2700K/3000K/3500K/4000K/5000K	81LM/W	5"