

GL-MCTP
MCTP

120-277V

TECHNICAL SPECIFICATIONS:

- :: Output Power & CCT are tuneable (Remote Control needed)
- :: Die-cast aluminum with powder coat finish optimized for LED
- :: Optical Lens: Plaid Tempered Glass + Aluminum Reflectors
- :: Power range: 0-80W (Adjustable with remote control)
- :: Lumens range: 0-9000LM (Adjustable with remote control)
- :: Voltage: 120-277V
- :: Four 1/2" hubs: 1 top, 1 on each side, 1 rear
- :: Chip: Philips Lumileds LEDs
- :: Lumens: 80LM/W
- :: CRI: >80
- :: Power Factor: >0.92
- :: Operating Temp: -40°F to 104°F
- :: 70,000 hour rated life
- :: 7-year warranty
- :: Suitable for Wet Locations, IP65



GL-MCTP-BK



GL-MCTP-BR





MCTP-RC1
Not Included



GL-MCTP-WH

APPLICATIONS:

- :: The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations



LED GARDEN TUNEABLE FLOOD LIGHTS WITH KNUCKLE

CATALOG NO.	WATTS	LPW	COLOR TEMP	DIMENSIONS
GL-MCTP-BK	0-20W	70LM/W	3000K~5700K	6 3/4"(H) x 5"(W) x 5 1/2"(D)
GL-MCTP-BR	0-20W	70LM/W	3000K~5700K	6 3/4"(H) x 5"(W) x 5 1/2"(D)
GL-MCTP-WH	0-20W	70LM/W	3000K~5700K	6 3/4"(H) x 5"(W) x 5 1/2"(D)