

# STL3

## TECHNICAL SPECIFICATIONS:


- :: Die-cast aluminum with powder coat finish (Light Grey)
- :: Lens Type: Optical TYPE III Lens, High light transmittance PC, anti-UV and flame resistant
- :: Voltage: 120-277V; 60Hz AC & 480V
- :: With NEMA twist-lock photocell socket (shorting cap incl.)
- :: Cord type: 40" SJTW 18/3 AWG cable
- :: With 2-15/16" diameter pole entry with adapter bracket inside for smaller pole diameters
- :: Driver located in isolated compartment for improved thermal management
- :: CRI: >70
- :: 50,000 hour rated life
- :: 7-year warranty
- :: Suitable for Wet Locations, IP65



Shown with photocell  
(Not Included)



STL2-WMA



## LED STREET/ROADWAY LIGHTS WITH NEMA TWIST-LOCK PHOTOCELL SOCKET

CATALOG NO.	WATTS	LPW	COLOR TEMP	VOLTAGE	DIMENSIONS
STL3-30W-30K	30W	130 LM/W	3000K	120-277	14 1/2"(L) x 6 4/5"(W) x 3 1/5"(H)
STL3-30W-50K	30W	130 LM/W	5000K	120-277	14 1/2"(L) x 6 4/5"(W) x 3 1/5"(H)
STL3-50W-30K	50W	135 LM/W	3000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-50W-50K	50W	135 LM/W	5000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-80W-30K	80W	135 LM/W	3000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-80W-50K	80W	135 LM/W	5000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-100W-30K	100W	135 LM/W	3000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-100W-50K	100W	135 LM/W	5000K	120-277	18 1/5"(L) x 9"(W) x 4 1/2"(H)
STL3-150W-30K	150W	140 LM/W	3000K	120-277	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-150W-50K	150W	140 LM/W	5000K	120-277	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-200W-30K	200W	135 LM/W	3000K	120-277	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-200W-50K	200W	135 LM/W	5000K	120-277	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-90W-50K-480V	90W	150 LM/W	5000K	480	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-150W-50K-480V	150W	150 LM/W	5000K	480	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL3-200W-50K-480V	200W	135 LM/W	5000K	480	21 4/5"(L) x 12 1/4"(W) x 4 4/5"(H)
STL2-WMA	WALL MOUNTING ARM 19 3/5" LENGTH				