

# R12V

## I2-VOLT

### HIGH OUTPUT



R12V-5M-D5-CW



R12V-5M-D5-P65-WW

#### TECHNICAL SPECIFICATIONS:

- :: LED: SMD3528 chip spaced 5/8" on center, 19 per foot, .08 watts each chip
- :: Dimmable using a magnetic driver
- :: Cutting increment: Every 3 LEDs,
- :: Working voltage: 12V DC (LED driver required)
- :: Power: 1.5 watts per foot
- :: CRI: 80, maximum run is 40 feet
- :: 120° beam angle
- :: 3M double sided tape is pre-installed under each ribbon
- :: Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)

#### Application:

- :: Ideal for undercabinet, soffit, display cases and toe kick lighting.

F2

12V HIGH OUTPUT LED RIBBON



## 12V INDOOR HIGH OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
R12V-5M-D5-CW	5500K	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.
R12V-5M-D5-WW	3200K	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.
R12V-5M-D5-RGB	RGB COLOR CHANGING	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.



## 12V WET LOCATION HIGH OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
R12V-5M-D5-P65-CW	5500K	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.
R12V-5M-D5-P65-WW	3200K	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.
R12V-5M-D5-P65-RGB	RGB COLOR CHANGING	4.4	16.4 ft.	254	19	1/2 in.	SMD5050	16 ft.

