

R24V

24-VOLT

STANDARD OUTPUT



R24V-5M-D3-CW

TECHNICAL SPECIFICATIONS:

- :: Material: silicon copper membrane
- :: LED: SMD3528 chip spaced 5/8" on center, 19 per foot, .08 watts each chip
- :: Dimmable using a magnetic driver
- :: Cutting increment: Every 4 inches
- :: Working voltage: 24V DC (LED driver required)
- :: Power: 1.5 watts per foot
- :: Lumens: 90 lumens per foot, 4.73 LM per LED
- :: CRI: 80
- :: Max run: 80'
- :: 120° beam angle
- :: 3M double sided tape is preinstalled
- :: Includes 1 female ribbon-to-power supply connector (Prewired) and 1 male plug for connection to next ribbon (Prewired)

Application:

- :: Ideal for undercabinet, soffit, display cases and toe kick lighting.

F3

24V STANDARD OUTPUT LED RIBBON



24V INDOOR STANDARD OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
R24V-5M-D3-CW	5500K	1.5	16.4 ft.	90	19	7/16 in.	SMD3528	80 ft.
R24V-5M-D3-WW	3200K	1.5	16.4 ft.	90	19	7/16 in.	SMD3528	80 ft.



24V INDOOR (98.4FT ROLLS) STANDARD OUTPUT LED RIBBON

CATALOG NO.	COLOR TEMP	WATTS PER FT.	REEL LENGTH	LUMENS PER FT.	LEDs PER FT.	WIDTH	LED TYPE	MAX RUN
R24V-30M-D3-CW	5500K	1.5	98.4 ft.	90	19	7/16 in.	SMD3528	80 ft.
R24V-30M-D3-WW	3200K	1.5	98.4 ft.	90	19	7/16 in.	SMD3528	80 ft.

Note: For best results, connect each 32' section to the power supply

