


Dimmable LED Flood Lights




A.



10 1/4"(W) x 9 1/2"(H) x 9"(D)




B.



10 1/4"(W) x 9 1/2"(H) x 9"(D)




C.



10 1/4"(W) x 9 1/2"(H) x 9"(D)




D.



10 1/4"(W) x 9 1/2"(H) x 9"(D)




E.



10 1/4"(W) x 9 1/2"(H) x 9"(D)



F.



10 1/4"(W) x 9 1/2"(H) x 9"(D)

Wattage

20W / 30W

Voltage Input

120VAC, 50/60Hz

Efficacy

95LM/W


Dimming

0~10V Dimmable


Finish

Die-cast aluminum with powder coat finish
Bronze / White


Color Temperatures




3000K



4000K



5000K



5700K

Features



Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.
SL-10W-50K-BZ-D	A.	SL-20W-50K-BZ-D	C.	SL-20W-30K-WH-D	D.	SL-30W-MCT-WH-D	E.
SL-10W-30K-BZ-D	A.	SL-20W-30K-BZ-D	C.	SL-20W-MCT-WH-D	D.		
SL-10W-50K-WH-D	B.	SL-20W-MCT-BZ-D	G.	SL-30W-50K-BZ-D	E.		
SL-10W-30K-WH-D	B.	SL-20W-50K-WH-D	D.	SL-30W-30K-WH-D	F.		