

T5


A/C Direct (Ballast Override)
OR
With Ballast




TECHNICAL SPECIFICATIONS:

- :: T5 LED lamp, operates A/C Direct (Ballast override) (T5-TYPB version) or with ballasts (T5-TYPA version).
- :: Voltage: 120V AC input
- :: Rated for use in open fixtures only. Not for use in enclosed fixtures
- :: UL-listed, DLC-rated
- :: Power Factor: 90%
- :: Total Harmonic Distortion: ≤20 %
- :: Beam Spread: 120°
- :: Base: Fits standard T5 sockets
- :: Rated Life: 50,000 hrs, 5-year warranty
- :: Ambient Operating Temperature: -4°F to 104°F
- :: CRI: 82
- :: Ideal for offices, retail stores, showrooms, and residential applications. Especially suited for areas where accessing the fixture is challenging.

B38




For four/three lamp application need to put the black/white and black wires together



For two lamp application cap any black/white lead

(T5-TYPA wiring diagram)



For four/three lamp application need to put the black/white and black wires together

(T5-TYPB wiring diagram)



4FT. LED T5 GLASS TUBE LAMPS

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	INSTALLATION TYPE	FINISH	LENGTH
T5-TYPA-27W-40K-F	27W	3200LM	4000K	Type A W/ Ballast	Frosted	4FT.
T5-TYPA-27W-50K-F	27W	3200LM	5000K	Type A W/ Ballast	Frosted	
T5-TYPB-25W-40K-F	25W	3200LM	4000K	Type B Ballast Override	Frosted	
T5-TYPB-25W-50K-F	25W	3200LM	5000K	Type B Ballast Override	Frosted	