## UCA **ADJUSTABLE ANGLE** MULTI COLOR TEMPERATURE



## TECHNICAL SPECIFICATIONS:


- :: Linkable
- :: 1/2" KOs for hardwiring instalation (multiple on top and back)
- :: Standard
- :: Built-in LED driver
- :: Available in 5 lengths: 12", 21", 24", 33", 42"
- :: 22-gauge sheet metal housing, white or bronze enamel finish, painted after fabrication
- :: Very low, 1" profile, only 3-1/2" wide
- :: Tempered glass lens for easy cleaning, inside frosted to reduce LED imaging
- :: Adjustable color temperature
- :: CRI = 84
- :: Working voltage: 120V with plug and hardwire option included
- :: Color packaging with hanging tab
- :: 3/8" flex connector and mounting screws included
- :: Includes 6' power cord with plug and (1) 8" Interconnect cable
- :: Key-holed mounting slots in housing simplify installation

## FEATURES:

- :: LEDs offer incredible brightness, energy efficiency and color rendering.
- :: Low heat, easy installation, environmentally friendly and maintenance free for many years
- :: Ideal for under cabinet, display cases or in low profile areas



**UCA-WHT** 



6' Power Cord 8" Interconnect Cable **Mounting Screws** 



On/Off Switch with 100%/50% Dimming Color Temp. Switch: 2700K/3000K/4000K



1/2" KOs Cable Connector included

## 120-VOLT LED UNDERCABINET

CATALOG NO.	LENGTH	COLOR TEMP	WATTS	LUMENS	FINISH
UCA-12-WHT	12"	2700K/3000K/4000K	5W	275LM	White
UCA-21-WHT	21"	2700K/3000K/4000K	8W	450LM	White
UCA-24-WHT	24"	2700K/3000K/4000K	12W	650LM	White
UCA-33-WHT	33"	2700K/3000K/4000K	16W	900LM	White
UCA-42-WHT	42"	2700K/3000K/4000K	20W	1100LM	White
UCA-12-BRZ	12"	2700K/3000K/4000K	5W	275LM	Bronze
UCA-21-BRZ	21"	2700K/3000K/4000K	8W	450LM	Bronze
UCA-24-BRZ	24"	2700K/3000K/4000K	12W	650LM	Bronze
UCA-33-BRZ	33"	2700K/3000K/4000K	16W	900LM	Bronze
UCA-42-BRZ	42	2700K/3000K/4000K	20W	1100LM	Bronze

