

24-Volt Indoor LED Ribbon Lights Extra High Output



A. 16.4'(L) x 0.4"(W)



B. 98.4'(L) x 0.4"(W)



C. 98.4'(L) x 0.4"(W)

Wattage

6.7W / 8.8W Per Ft.

Voltage Input

24VDC (LED Driver Required)

Efficacy

70-79 LM/W Per Ft.

Dimming

Dimmable Using a Magnetic Driver

Finish

Cutting Increment: Every 2 Inches
 1 Female Ribbon-to-Power Supply Connector & 1 Male Plug
 for Connection to Next Ribbon
 Max Run: 11Ft. / 14Ft.

Color Temperatures



Beam Angles



Features



Catalog No.	Fig.	Catalog No.	Fig.	Catalog No.	Fig.
ULR-IN-16F-XHO-27K	A.	ULR-IN-98F-XHO-27K	B.	ULR-IN-16F-YHO-27K	C.
ULR-IN-16F-XHO-30K	A.	ULR-IN-98F-XHO-30K	B.	ULR-IN-16F-YHO-30K	C.
ULR-IN-16F-XHO-40K	A.	ULR-IN-98F-XHO-40K	B.	ULR-IN-16F-YHO-40K	C.
ULR-IN-16F-XHO-50K	A.	ULR-IN-98F-XHO-50K	B.	ULR-IN-16F-YHO-50K	C.