

WML2

A3

LED NON-CUTOFF WALL PACKS SECOND GENERATION



Bottom LED array ensures seamless coverage in proximity of the fixture

TECHNICAL SPECIFICATIONS:

- :: Die-cast aluminum housing with powder coat finish (Dark Bronze)
- :: Same footprint as traditional HID wall packs
- :: Prismatic borosilicate glass lens
- :: Includes mounting hardware
- :: Four 1/2" hubs: 1 top, 1 on each side, 1 rear
- :: Chip: Lumileds LEDs
- :: CRI: >70
- :: Power Factor: 95%
- :: Operating Temp: -4°F to 104°F
- :: 50,000 hour rated life
- :: 5-year warranty
- :: Suitable for Wet Locations, IP65

APPLICATIONS:

- :: Ideal for general site lighting, alleys, loading docks, doorway, pathway and parking areas



LED NON-CUTOFF WALL PACKS SECOND GENERATION

CATALOG NO.	WATTS	LUMENS	COLOR TEMP	REPLACEMENT RANGE	DIMENSIONS
WML2-28W-50K-HL-SM	28W	3400LM	5000K	100~150 MH	10"(W) x 5-3/4"(H) x 5-1/2"(D)
WML2-28W-40K-HL-SM	28W	3400LM	4000K	100~150 MH	
WML2-28W-30K-HL-SM	28W	3400LM	3000K	100~150 MH	
WML2-50W-50K-SM	50W	5600LM	5000K	100~200 MH	
WML2-50W-40K-SM	50W	5600LM	4000K	100~200 MH	14-1/4"(W) x 9-1/4"(H) x 7-3/8"(D)
WML2-50W-30K-SM	50W	5600LM	3000K	100~200 MH	
WML2-50W-50K-HL	48W	6500LM	5000K	175~250 MH	
WML2-50W-40K-HL	48W	6500LM	4000K	175~250 MH	
WML2-50W-30K-HL	48W	6500LM	3000K	175~250 MH	18-1/2"(W) x 9"(H) x 8-1/2"(D)
WML2-80W-50K-HL	80W	10100LM	5000K	250~400 MH	
WML2-80W-40K-HL	80W	10100LM	4000K	250~400 MH	
WML2-80W-30K-HL	80W	10100LM	3000K	250~400 MH	
WML2-120W-50K-HL-LG	120W	15900LM	5000K	250~450 MH	18-1/2"(W) x 9"(H) x 8-1/2"(D)
WML2-120W-40K-HL-LG	120W	15900LM	4000K	250~450 MH	
WML2-120W-30K-HL-LG	120W	15900LM	3000K	250~450 MH	
WML2-150W-50K-LG	150W	18000LM	5000K	250~450 MH	
WML2-150W-40K-LG	150W	18000LM	4000K	250~450 MH	18-1/2"(W) x 9"(H) x 8-1/2"(D)
WML2-150W-30K-LG	150W	18000LM	3000K	250~450 MH	

