CIGL SERIES Outdoor Lighting

CIGL-40-MCT
LINEAR ARCHITECTURAL INGROUND LIGHTS, 3CCT
Multi Color Temperature (Selectable)




Customer Name:

Project Name:

Note: Type:





Illuminate large areas with our Commercial Large Wall/Step Lighting. Engineered for high-traffic commercial environments, this fixture offers bright, uniform light with energy-efficient LED technology. Its robust, weather-resistant construction ensures durability, while versatile mounting options allow for seamless installation on walls or steps. Perfect for enhancing safety and visibility in any commercial setting.

3.9"(H) x 39.37"(W) x 2.76"(D)

Features

Die-Cast Aluminum With Powder Coat Finish

- Lens: Prismatic Lens
- 7-Year Warranty

Technical Specifications

Electrical:

Voltage: 120~277 VAC, 50/60 Hz

Wattage: 24WPower Factor: >0.95Efficacy: 94LM/W

Mechanical:

- Die-Cast Aluminum With Powder Coat Finish
- Recessed Wall Mount
- Traffic Rated: Designed to withstand heavy vehicular loads, ensuring durability and reliability in high-traffic areas. Ideal for parking lots, driveways, and roadways
- Can Be Installed In Concrete
- Operating Temperature: -40°F to 10°F
- 7-Year Warranty
- IP 65. Suitable for Wet Locations

Lighting:

- MCT: CCT Selectable Switch Inside the Fixture
- Lens: Prismatic Lens
- Total Lumens: 2256LM Max.
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 64°Rated life: 70,000 Hrs

Applications:

- Alleys
- Loading Docks
- Doorways
- Pathways
- Parking areas
- · Residential area

Other Models:

• 5W | 420LM | CIGL-9-MCT

• 10W | 860LM | CIGL-20-MCT











Other Views: CIGL-40-MCT



Performance Table: CIGL-40-MCT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	LPW
CIGL-40-MCT	24W	120~277V	2256LM	3000K 4000K 5000K	94

Sample Ordering

Model		Size	Color Temp.	
CIGL	_[40	– MCT	



