## CIGL SERIES Outdoor Lighting

CIGL-9-MCT LINEAR ARCHITECTURAL INGROUND LIGHTS, 3CCT







Illuminate large areas with our Commercial Large Wall/Step Lighting. Engineered for high-traffic commercial environments, this fixture offers bright, uniform light with energy-efficient LED technology. Its robust, weather-resistant construction ensures durability, while versatile mounting options allow for seamless installation on walls or steps. Perfect for enhancing safety and visibility in any commercial setting.



Customer Name:	
Project Name:	
Note:	Type:





3.9"(H) x 9"(W) x 2.7"(D)

## **Features**

Die-Cast Aluminum With Powder Coat Finish

- Lens: Prismatic Lens
- 7-Year Warranty

## **Technical Specifications**

#### **Electrical:**

Voltage: 120~277 VAC, 50/60 Hz

Wattage: 5W

Power Factor: >0.95Efficacy: 84LM/W

#### **Mechanical:**

- Die-Cast Aluminum With Powder Coat Finish
- Recessed Wall Mount
- Traffic Rated: Designed to withstand heavy vehicular loads, ensuring durability and reliability in high-traffic areas. Ideal for parking lots, driveways, and roadways
- Can Be Installed In Concrete
- Operating Temperature: -40°F to 10°F
- 7-Year Warranty
- IP 65, Suitable for Wet Locations

### Lighting:

- MCT: CCT Selectable Switch Inside the Fixture
- Lens: Prismatic Lens
- Total Lumens: 420LM Max.
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 64°
- Rated life: 70,000 Hrs

### Applications:

- Alleys
- Loading Docks
- Doorways
- Pathways
- Parking areas
- Residential area

#### Other Models:

• 10W | 860LM | CIGL-20-MCT

• 24W | 2256LM | CIGL-40-MCT











# Other Views: CIGL-9-MCT





Side View Front View

Performance Table: CIGL-9-MCT

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	LPW
CIGL-9-MCT	5W	120~277V	420LM	3000K 4000K 5000K	84

# Sample Ordering

Model		Size	Color Temp.	
CIGL	<b>  -</b> [	9	<b>–</b> MCT	

