



E26
Medium Base



Samsung
LM561B



Rubycon



E26



JAE Connector

DIMENSIONS:



10-1/2" (H) x 3-3/4" (Dia)

- Reliability Test
- Safety Protection Circuit
- No Mercury
No UV Light
- Big Saving (87%)
on Electricity Costs
- Usable in Enclosed
Luminaires
- Omni Wide Angle

CL-54W-30K
CL-54W-50K

Corn Lamps

Ideal for retrofitting existing HID highbay, shoebox, flood light, or wall pack fixtures. The lamps can be used in enclosed luminaires.

MODEL NO	WATTAGE	LUMENS	VOLTAGE	COLOR TEMP
CL-54W-30K	54W	5440	120-277V AC	3000K
CL-54W-50K	54W	5700	120-277V AC	5000K

ELECTRICAL SPECIFICATIONS:

- Voltage: AC120~277V 50~60Hz
- Wattage: LED consumption: 54W
- Other wattages available: 18W, 36W, 120W
- Power factor: >0.9

LIGHTING SPECIFICATIONS:

- LED type: Samsung LED chips with Rubycon driver
- LED chips quantity: 56 LEDs 0.3W
- Total lumens: 30K 5440/ 50K 5700
- Color temperature: 30K 3000K/ 50K 5000K
- Color rendering index: 84
- Beam angle: 360°

OTHERS:

- Net weight: 2.1lbs / 955g
- Gross weight per CTN: 30.9lbs / 14kg

HOUSING SPECIFICATIONS:

- Lamp base: E26 medium base for CL-54W
- E39 mogul base for CL-120W
- Wet locations: IP65 weatherproof
- Operating temperature: -20~+65 °C
- Storage temperature: -40~+80

WARRANTY:

- 5 years
- 50,000-hour design life

CERTIFICATIONS:

- Certifications: UL/cUL



CL-54W-30K

CL-54W-50K

Corn Lamps

MODEL NO	WATTAGE	LUMENS	VOLTAGE	COLOR TEMP
CL-54W-30K	54W	5440	120-277V AC	3000K
CL-54W-50K	54W	5700	120-277V AC	5000K



PHOTOMETRICS:

Luminous emittance

