


CL-EHL SERIES Industrial Lighting

CL-EHL-45W-30K-E39
CL-EHL-45W-50K-E39



Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



9 6/7"(H) x 3 1/3"(W)

LED Corn Lamp suitable for supermarkets, warehouses, garages, home, offices, hotels, hospitals, schools, high bay retrofitting

Features

- E39 Mogul Base
- 5-Year Warranty
- Housing: PC + Aluminum
- 50,000 Hours Rated Life

Technical Specifications

Electrical:

- Voltage: 120-277V AC 50/60Hz
- Wattage: 45W
- Power Factor: >0.9
- AC Direct / Bypass Existing Ballast
- THD: ≤20%
- Efficacy: 125/155 LPW

Mechanical:

- PC and Aluminum housing and Sealant pouring for whole driver
- E39 Mogul Base
- Operating temperature: -40°F to 176°F
- Minimum Enclosed Space Dimension: 15.0"(H) x 7.9"(D) and 928 Cubic in
- Suitable for Damp Location

Lighting:

- LED Type: SMD2835
- Total lumens: 5625LM/6975LM
- Color temperature: 3000K/5000K
- Color rendering index: >80
- Beam angle: 360°
- Replacement Range: 70-100MH

Applications:


- LED Corn Lamp suitable for supermarkets, warehouses, garages, home, offices, hotels, hospitals, schools, highbay retrofitting

Other Models:


- | | | |
|--------------------------------------|--|--|
| • 12W 1500LM CL-EHL-12W-30K-E26 | • 18W 2250LM CL-EHL-18W-30K-E26 | • 27W 3375LM CL-EHL-27W-30K-E26 |
| • 12W 1860LM CL-EHL-12W-50K-E26 | • 18W 2610LM CL-EHL-18W-50K-E26 | • 27W 4185LM CL-EHL-27W-50K-E26 |
| • 36W 4500LM CL-EHL-36W-30K-E26 | • 36W 4500LM CL-EHL-36W-30K-E39 | • 54W 6750LM CL-EHL-54W-30K-E39 |
| • 36W 5580LM CL-EHL-36W-50K-E26 | • 36W 5580LM CL-EHL-36W-50K-E39 | • 54W 8370LM CL-EHL-54W-50K-E39 |
| • 75W 9375LM CL-EHL-75W-30K-E39 | • 100W 12500LM CL-EHL-100W-30K-E39 | • 120W 15600LM CL-EHL-120W-30K-E39 |
| • 75W 11625LM CL-EHL-75W-50K-E39 | • 100W 15500LM CL-EHL-100W-50K-E39 | • 120W 17400LM CL-EHL-120W-50K-E39 |



Photometrics: CL-EHL-45W-E39



BUD Rating: B2-U4-G3



45W, 5000K Area 65'x 65' Mounting Height: 9'

Other Views:



Side View



Front View

Performance Table: CL-EHL-45W-E39

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CL-EHL-45W-30K-E39	45W	120~277V	5625	3000K	B2-U4-G3	125
CL-EHL-45W-50K-E39	45W	120~277V	6975	5000K	B2-U4-G3	155

Sample Ordering

Model Style Wattage Color Temp. Base

CL - EHL - 45W - - E39

30K = 3000K
50K = 5000K

Accessory:

Blank = No Option For Accessories
E39-REDUCER = REDUCES E39 BULB TO BE USED IN E26 SOCKET

ACCESSORY:



E39-REDUCER

Example:

- CL-EHL-45W-30K-E39 (FOR CL EHL 45W 30K FIXTURE 120-277V)
- CL-EHL-45W-30K-E39 (FOR CL EHL 45W 30K FIXTURE 120-277V)
E39-REDUCER (REDUCES E39 BULB TO BE USED IN E26 SOCKET)

