

CRLC SERIES

COMMERCIAL INDOOR LIGHTING

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

CRLC4-15W-MCT-S-D

CRLC4-15W-MCT-S-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT



Selection:




Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



4" (H) X 6 1/3" (W)

Features

- 4" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- Mounting Options: Recessed
- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

- Voltage: 120-277VAC 50/60Hz
- Wattage: 15W
- Power factor: >0.90
- Efficacy: 85 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1275LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

- Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 20W | 1720LM | CRLC4-20W-MCT-S-D
- 20W | 1720LM | CRLC4-20W-MCT-S-D-WH






Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com



WG-Z7-2D-2Z

Photometrics: CRLC4-15W-MCT-S-D



BUG Rating: B1-U1-G0


15W 5000K, Area 25" x 25" Mounting Height: 9'

Other Views:

Hazel



CRLC-EGN-15W-MCT-D



CRLC-TRM-4S




CRLC4-15W-MCT-S-D

Whitev



CRLC-EGN-15W-MCT-D



CRLC-TRM-4S-WH



CRLC4-15W-MCT-S-D-WH

Performance Table: CRLC4-15W-MCT-S-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-15W-MCT-S-D	15W	120-277V	1275LM	3000K	B1-U1-G0	85
CRLC4-15W-MCT-S-D-WH				4000K		
				5000K		

Sample Ordering

Model Watt Shape Dimming Housing

CRLC4 - 15W - MCT - S - D - []

Blank
WH = WHITE

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



OPT-EM-HB1EXT
EXTERNAL EMERGENCY
BACK UP BATTERY

Example:

- CRLC4-15W-MCT-S-D (FOR 15W CRLC4 MCT 120-277V)
- CRLC4-15W-MCT-S-D OPT-EM-HB1EXT (FOR 15W CRLC4 MCT 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)

