CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-15W-MCT-SA-D CRLC4-15W-MCT-SA-D-WH

4" LED COMMERCIAL SQUARE & WALL WASH RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name:

Project Name:

Note: Type:



6 1/4"(H) X 4" (W)

Features

- 4" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- · Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz

Wattage: 15WPower factor: >0.90Efficacy: 85 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1275LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 20W | 1720LM | CRLC4-20W-MCT-SA-D
- 20W | 1720LM | CRLC4-20W-MCT-SA-D-WH













Photometrics: CRLC4-15W-MCT-SA-D





20 15 10 2fc 1fc 0.5fc 0.1fc 10 25

BUG Rating: B1-U1-G0

15W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:











CRLC-TRM-4SA

CRLC4-15W-MCT-SA-D

White







CRLC-TRM-4SA-WH



CRLC4-15W-MCT-SA-D-WH

Performance Table: CRLC4-15W-MCT-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-15W-MCT-SA-D	15/4/	120-277V	1275LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC4-15W-MCT-SA-D-WH	15W					

Sample Ordering

Model	Watt	Shape Dimmin	g	Housing
CRLC4	– 15W	- MCT - SA - D]_	
				Blank

WH = WHITE

Accessory:



Accessory:

Blank = No Option For Accessories SSL-346-RIBH = 3",4",6" (ADJUSTABLE)SQUARE GALVANIZED PLATE WITH BAR HANGERS

Factory-Installed Option:

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:







