CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-20W-MCT-S-D CRLC4-20W-MCT-S-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name:

Project Name:



4"(H) X 6 1/3" (W)

-eatures

- 4" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz

Wattage: 20W Power factor: >0.90 Efficacy: 85 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1720LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 15W | 1275LM | CRLC4-15W-MCT-S-D
- 15W | 1275LM | CRLC4-15W-MCT-S-D-WH













Photometrics: CRLC4-20W-MCT-S-D





20 15 10 2fc 1fc 0.5fc 0.1fc 10 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:












CRLC-EGN-20W-MCT-D CRLC-TRM-4S

CRLC4-20W-MCT-S-D

White







CRLC-TRM-4S-WH



CRLC4-20W-MCT-S-D-WH

Performance Table: CRLC4-20W-MCT-S-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-20W-MCT-S-D	20W	120-277V	1720LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC4-20W-MCT-S-D-WH						

Sample Ordering

Shape Dimming Housing Model Watt CRLC4 - 20W - MCT -Blank

WH = WHITE

Factory-Installed Option:



Factory-Installed Option:

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Example:

1. CRLC4-20W-MCT-S-D

(FOR 20W CRLC4 MCT 120-277V)

1. CRLC4-20W-MCT-S-D OPT-EM-HB1EXT

(FOR 20W CRLC4 MCT 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





