# CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-20W-MCT-S-D CRLC4-20W-MCT-S-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

**Customer Name:** 

Project Name:



4"(H) X 6 1/3" (W)

# -eatures

- 4" Haze & White Finish TRIM
- MCT: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

# **Technical Specifications**

#### **Electrical:**

Voltage: 120-277VAC 50/60Hz

Wattage: 20W Power factor: >0.90 Efficacy: 85 LPW

## Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

## Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1720LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

# **Applications:**

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

#### Other Models:

- 15W | 1275LM | CRLC4-15W-MCT-S-D
- 15W | 1275LM | CRLC4-15W-MCT-S-D-WH













# Photometrics: CRLC4-20W-MCT-S-D





25 20 15 10 5 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

### Other Views:










CRLC-TRM-4S



CRLC4-20W-MCT-S-D

White







CRLC-TRM-4S-WH



CRLC4-20W-MCT-S-D-WH

## Performance Table: CRLC4-20W-MCT-S-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-20W-MCT-S-D	20W	120-277V	1720LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC4-20W-MCT-S-D-WH						

# Sample Ordering

Model Watt Shape Dimming Housing

CRLC4 = 20W = MCT = S = D =

Blank WH = WHITE

#### Accessory:



SSL-346-RIBH

### **Accessory:**

Blank = No Option For Accessories SSL-346-RIBH = 3",4",6" (ADJUSTABLE)SQUARE GALVANIZED PLATE WITH BAR HANGERS

# **Factory-Installed Option:**

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

#### **Factory-Installed Option:**







