CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-40W-MCTP-D CRLC4-40W-MCTP-D-WH


4" LED COMMERCIAL RECESSED LIGHT



Customer Name:

Project Name:

Note: Type:



10 1/2"(L) X 4 1/7"(W) X 5 1/2" (D)

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Features

- 4" Haze & White Finish TRIM
- MCTP: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277V AC 50/60Hz

27W/34W/40WPower factor: >0.90Efficacy: 80 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

Selection:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 3200LM Max.
- Color temperature: 3000K/3500K/4000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 40W | 3200LM | CRLC4-40W-MCTP-A-D
- 40W | 3200LM | CRLC4-40W-MCTP-A-D-WH













Photometrics: CRLC4-40W-MCTP-D





25 20 15 10 5 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:





CRLC-EGN-40W-MCTP-D





=



CRLC-TRM-4

CRLC4-20W-MCT-D

White









CRLC-TRM-4-WH



CRLC4-20W-MCT-D-WH

Performance Table: CRLC4-40W-MCTP-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-40W-MCTP-D	27W	120-277V	2160LM	3000K 3500K 4000K	B1-U1-G0	80
CRLC4-40W-MCTP-D-WH	34W		2720LM			
	40W		3200LM			

Sample Ordering

Model	Watt	Dir	nming	Housing
CRLC4	– 40W –	MCTP =	D	_
				Blank WH = WHITE

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



Example:

1. CRLC4-40W-MCTP-D

(FOR 40W CRLC4 MCTP 120-277V)

1. CRLC4-40W-MCTP-D OPT-EM-HB1EXT (FOR 40W CRLC4 MCTP 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





