CRLC SERIES COMMERCIAL INDOOR LIGHTING




CRLC4-40W-MCTP-SA-D CRLC4-20W-MCTP-SA-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.



Project Name:



7 1/2"(H) X 6 1/3" (W)

eatures

- 4" Haze & White Finish TRIM
- MCTP: The Switch Is On The Light Engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277V AC 50/60Hz

Wattage: 27W/34W/40W Power factor: >0.90

Efficacy: 80 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed To Operate In Temperatures 113°F
- Housing Not Required. Two Spring Clips To Hold The Fixture In Place
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The Switch Is On The Light Engine
- Dimming: 0~10V Dimmable
- Total Lumens: 3200LM Max.
- Color Temperature: 3000K/3500K/4000K
- Color Rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 40W | 3200LM | CRLC4-40W-MCTP-S-D
- 40W | 3200LM | CRLC4-40W-MCTP-S-D-WH













Photometrics: CRLC4-40W-MCTP-SA-D





25 20 15 10 5 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









CRLC-EGN-40W-MCTP-D

CRLC-TRM-4SA

CRLC4-40W-MCTP-SA-D

White











CRLC4-40W-MCTP-SA-D-WH

Performance Table: CRLC4-40W-MCTP-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-40W-MCTP-SA-D	27W	120-277V	2160LM	3000K 3500K 4000K	B1-U1-G0	80
CRLC4-40W-MCTP-SA-D-WH	34W		2720LM			
	40W		3200LM			

Sample Ordering

Model Watt Color TempShape Dimming Housing CRLC4 = 40W = MCTP = SA = D =

Blank WH = WHITE

Factory-Installed Option:



OPT-EM-HB1EXT EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY



