CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-40W-MCTP-SA-D CRLC4-40W-MCTP-SA-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name:

Project Name:



7 1/2"(H) X 4 1/7" (W) X 6 1/3" (D)

Features

- 4" Haze & White Finish TRIM
- MCTP: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277V AC 50/60Hz

Wattage: 27W/34W/40WPower factor: >0.90

Efficacy: 80 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 3200LM Max.
- Color temperature: 3000K/3500K/4000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 40W | 3200LM | CRLC4-40W-MCTP-S-D
- 40W | 3200LM | CRLC4-40W-MCTP-S-D-WH













Photometrics: CRLC4-40W-MCTP-SA-D





20 15 10 2fc 1fc 0.5fc 0.1fc 10 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:











CRLC4-40W-MCTP-SA-D

CRLC-EGN-40W-MCTP-D CRLC-TRM-4SA

White



CRLC-EGN-40W-MCTP-D





CRLC-TRM-4SA-WH



CRLC4-40W-MCTP-SA-D-WH

Performance Table: CRLC4-40W-MCTP-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-40W-MCTP-SA-D	27W		2160LM	3000K		
	34W	120-277V	2720LM	3500K	B1-U1-G0	80
CRLC4-40W-MCTP-SA-D-WH	40W		3200LM	4000K		

Factory-Installed Option:

OPT-EM-HB1EXT

EXTERNAL EMERGENCY

BACK UP BATTERY

Sample Ordering

Watt Color TempShape Dimming Housing

CRLC4 | = |40W| = |MCTP| = | SA |

Blank WH = WHITE

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:

Example: 1. CRLC4-40W-MCTP-SA-D

Model

1. CRLC4-40W-MCTP-SA-D OPT-EM-HB1EXT

(FOR 40W CRLC4 MCTP 120-277V)

(FOR 40W CRLC4 MCTP 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)



