CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC4-60W-MCTP-S-D CRLC4-60W-MCTP-S-D-WH

4" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT

MITP Multi Color Temperature (Selectable)

Customer Name: Project Name: Note: Type:



Avail. Finishes:

a 83.0 6 1/3" _ 5"

7 1/2"(H) X 6 1/3" (W)

LED COMMERCIAL RECESSED LIGHT offers energy-efficient, high-performance illumination designed for commercial spaces, ensuring durability and optimal lighting quality.

eatures

- 4" Haze & White Finish TRIM
- MCTP: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277V AC 50/60Hz Wattage: 40W/50W/60W Power Factor: >0.90

Efficacy: 80 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable Total lumens: 4800LM Max.
- Color Temperature: 3000K/3500K/4000K
- Color Rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.













Photometrics: CRLC4-60W-MCTP-S-D





15 10 2fc 1fc 0.5fc 0.1fc o 10

BUG Rating: B1-U1-G0

40W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









CRLC-EGN-60W-MCTP-D

CRLC-TRM-4S

CRLC4-60W-MCTP-S-D

White



CRLC-EGN-60W-MCTP-D





CRLC-TRM-4S-WH




CRLC4-60W-MCTP-SA-D-WH

Performance Table: CRLC4-60W-MCTP-S-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC4-60W-MCTP-S-D CRLC4-60W-MCTP-S-D-WH	40W 50W 60W	120-277V	3200LM 4000LM 4800LM	3000K 3500K 4000K	B1-U1-G0	80

Sample Ordering

Watt Color Temp. Shape Dimming Housing Model










Accessory:



CRLCS-46-RIBH-JB CRLC Square Mounting Plate With Brackets And J-Box 4/6 in



18 3/16"(W) x 12"(H) x 1/5"(D)

Accessory:

CRLCS-46-RIBH-JB = CRLC Square Mounting Plate With Brackets And J-Box 4/6 in

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-CRLC = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



OPT-EM-CRLC EXTERNAL EMERGENCY BACK UP BATTERY





