CRLC SERIES COMMERCIAL INDOOR LIGHTING




Type:

CRLC6-15W-MCT-A-D CRLC6-15W-MCT-A-D-WH

6" LED COMMERCIAL RECESSED LIGHT







6 1/2"(H) X 4 1/7"(W) X 7 3/5" (D)

Selection:

Ideal for hotel, offices, retail outlets, restaurant, parking garages,

Features

- 6" Haze & White Finish TRIM
- MCT: The switch is on the light engine

conference room, education facilities and more.

Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Customer Name:

Project Name:

Note:

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz

Wattage: 15WPower factor: >0.90Efficacy: 85 LPW

Mechanical:

- 4" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCT: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 1275LM
- Color temperature: 3000K/4000K/5000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Direct Fit 4 T8 LED tubes do not burn out easily and provide bright and even lighting to schools, office spaces, retail stores and storage rooms.

Other Models:

- 20W | 1720LM | CRLC6-20W-MCT-A-D
- 20W | 1720LM | CRLC6-20W-MCT-A-D-WH













Photometrics: CRLC6-15W-MCT-A-D





25 20 15 10 2fc 1fc 0.5fc 0.1fc 0 5 10 15 20 25

BUG Rating: B1-U1-G0

15W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









CRLC-TRM-6A



CRLC6-15W-MCT-A-D

White









CRLC-TRM-6A-WH



CRLC6-15W-MCT-A-D-WH

Performance Table: CRLC6-15W-MCT-A-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC6-15W-MCT-A-D	15W	120-277V	1275LM	3000K 4000K 5000K	B1-U1-G0	85
CRLC6-15W-MCT-A-D-WH						

Sample Ordering

Model Watt Color Temp. Dimming Housing

CRLC6 - 15W - MCT - A - D -

Blank WH = WHITE

Factory-Installed Option:

Blank = No Option For Accessories
OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



Example:

1. CRLC6-15W-MCT-A-D

(FOR 15W CRLC6 MCT 120-277V)

1. CRLC6-15W-MCT-A-D OPT-EM-HB1EXT (FOR 15W CRLC6 MCT 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





