CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC6-20W-MCTP-S-D CRLC6-20W-MCTP-S-D-WH

6" LED COMMERCIAL SQUARE & OPEN RECESSED LIGHT








Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Customer Name:

Project Name:







6"(H) X 4 1/7" (W)

Features

- 6" Haze & White Finish TRIM
- MCTP: Multi Color Temperature & Multi Power/Wattage (Selectable)
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60HzWattage: 10W/15W/20WPower Factor: >0.90

Efficacy: 86 LPW

Mechanical:

- 6" Haze & White Finish TRIM
- · Mounting Options: Recessed
- Temperature Rating: Designed To Operate In Temperatures 113°F
- IC-Rated
- Housing Not Required. Two Spring Clips To Hold The Fixture In Place
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: Multi Color Temperature & Multi Power/Wattage (Selectable)
- Dimming: 0~10V DimmableTotal Lumens: 1720LM
- Color Temperature: 3000K/3500K/4000K
- Color Rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 20W | 1720LM | CRLC6-20W-MCTP-S-D
- 20W | 1720LM | CRLC6-20W-MCTP-S-D-WH













Photometrics: CRLC6-20W-MCTP-S-D





20 15 10 5 2fc 1fc 0.5fc 0.1fc o 10 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

Other Views:









CRLC-TRM-6S



CRLC6-20W-MCTP-S-D

White







CRLC-TRM-6S-WH



CRLC6-20W-MCTP-S-D-WH

Performance Table: CRLC6-20W-MCTP-S-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC6-20W-MCTP-S-D	10W 15W 20W	120-277V	860LM	3000K	D4 114 C0	9.6
CRLC6-20W-MCTP-S-D-WH			1290LM 1720LM	3500K 4000K	B1-U1-G0	86

Model Watt **Shape Dimming Housing** CRLC6 | = |20W| = |MCTP| =

> Blank WH = WHITE

Accessory:

Blank = No Option For Accessories

SSL-346-RIBH = 3",4",6" (ADJUSTABLE)SQUARE GALVANIZED PLATE WITH BAR HANGERS

Factory-Installed Option:

Blank = No Option For Accessories

OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Accessory:



SSL-346-RIBH

Factory-Installed Option:









