# CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC6-20W-MCTP-SA-D CRLC6-20W-MCTP-SA-D-WH

6" LED COMMERCIAL SQUARE & WALL WASH RECESSED LIGHT






Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

# Customer Name:

Project Name:

Note: Type:



6 1/2"(H) X 7 1/2" (W)

# **Features**

- 6" Haze & White Finish TRIM
- MCTP: Multi Color Temperature & Multi Power/Wattage (Selectable)
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

# Technical Specifications

#### **Electrical:**

Voltage: 120-277VAC 50/60HzWattage: 10W/15W/20WPower Factor: >0.90

Efficacy: 86 LPW

#### Mechanical:

- 6" Haze & White Finish TRIM
- · Mounting Options: Recessed
- Temperature Rating: Designed To Operate In Temperatures 113°F
- No IC-Rated
- Housing Not Required. Two Spring Clips To Hold The Fixture In Place
- Suitable for Damp Locations
- 5-Year Warranty

### Lighting:

- MCTP: Multi Color Temperature & Multi Power/Wattage (Selectable)
- Dimming: 0~10V DimmableTotal Lumens: 1720LM
- Color Temperature: 3000K/3500K/4000K
- Color Rendering Index: >80
- Lifespan: 50,000 hrs.

#### **Applications:**

 Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

### Other Models:

- 20W | 1720LM | CRLC6-15W-MCTP-SA-D
- 20W | 1720LM | CRLC6-15W-MCTP-SA-D-WH













#### Photometrics: CRLC6-20W-MCTP-SA-D





20 15 10 5 2fc 1fc 0.5fc 0.1fc o 5 10 25

BUG Rating: B1-U1-G0

20W 5000K, Area 25" x 25' Mounting Height: 9'

#### **Other Views:**











CRLC-TRM-6S

CRLC6-20W-MCTP-S-D

White







CRLC-TRM-6S-WH



CRLC6-20W-MCTP-S-D-WH

#### Performance Table: CRLC6-20W-MCTP-SA-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC6-20W-MCTP-SA-D	10W 15W 20W	120-277V	860LM	3000K	D4 114 C0	0.0
CRLC6-20W-MCTP-SA-D-WH			1290LM 1720LM	3500K 4000K	B1-U1-G0	86

# Sample Ordering Model Watt Shape Dimming Housing

CRLC6 - 20W - MCTP - SA

Blank WH = WHITE

#### Accessory:





#### **Factory-Installed Option:**



**OPT-EM-HB1EXT EXTERNAL EMERGENCY** BACK UP BATTERY

## Accessory:

Blank = No Option For Accessories SSL6-RI = 6" SQUARE ROUGH-IN PLATE, 26" LONG

# **Factory-Installed Option:**

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

# Example:

1. CRLC6-20W-MCTP-SA-D 1. CRLC6-20W-MCTP-SA-D

(FOR 20W CRLC6 MCTP 120-277V)

(FOR 20W CRLC6 MCTP 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





