CRLC SERIES COMMERCIAL INDOOR LIGHTING



CRLC6-40W-MCTP-D CRLC6-40W-MCTP-D-WH

6" LED COMMERCIAL RECESSED LIGHT




Customer Name:

Project Name:

Note:

Selection:

Type:



Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

10 1/2"(L) X 4 1/7"(W) X 7 2/3" (D)

eatures

- 6" Haze & White Finish TRIM
- MCTP: The switch is on the light engine
- Mounting Options: Recessed

- 5-Year Warranty
- Lifespan: 50,000 hrs.

Technical Specifications

Electrical:

Voltage: 120-277VAC 50/60Hz

Wattage: 27W/34W/40W Power factor: >0.90 Efficacy: 85 LPW

Mechanical:

- 6" Haze & White Finish TRIM
- Mounting Options: Recessed
- Temperature Rating: Designed to operate in temperatures 113°F
- No IC-Rated
- Suitable for Damp Locations
- 5-Year Warranty

Lighting:

- MCTP: The switch is on the light engine
- Dimming: 0~10V Dimmable
- Total lumens: 3200LM Max.
- Color temperature: 3000K/3500K/4000K
- Color rendering index: >80
- Lifespan: 50,000 hrs.

Applications:

Ideal for hotel, offices, retail outlets, restaurant, parking garages, conference room, education facilities and more.

Other Models:

- 40W | 3200LM | CRLC6-40W-MCTP-D
- 40W | 3200LM | CRLC6-40W-MCTP-D-WH












Photometrics: CRLC6-40W-MCTP-D





30 15 10 2fc 1fc 0.5fc 0.1fc

BUG Rating: B1-U1-G0

20W 5000K, Area 30" x 30' Mounting Height: 9'

Other Views:











CRLC-EGN-40W-MCTP-D

CRLC-TRM-6

CRLC6-40W-MCTP-D

White



CRLC-EGN-40W-MCTP-D





CRLC-TRM-6-WH



CRLC6-40W-MCTP-D-WH

Performance Table: CRLC6-40W-MCTP-D

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
CRLC6-40W-MCTP-D	27W		2160LM	3000K		
	34W	120-277V	2720LM	3500K	B1-U1-G0	80
CRLC6-40W-MCTP-D-WH	40W		3200LM	4000K		

Sample Ordering

Model

Watt Color Temp.Dimming Housing

CRLC6 | = |40W| = | MCTP | =

Blank WH = WHITE

Factory-Installed Option:

Blank = No Option For Accessories OPT-EM-HB1EXT = EXTERNAL EMERGENCY BACK UP BATTERY

Factory-Installed Option:



Example:

1. CRLC6-40W-MCTP-D

(FOR 40W CRLC6 MCTP 120-277V)

1. CRLC6-40W-MCTP-D OPT-EM-HB1EXT

(FOR 40W CRLC6 MCTP 120-277V) (EXTERNAL EMERGENCY BACK UP BATTERY)





