

CXER SERIES OUTDOOR LIGHTING

CXER-40-80W-MCTP-SR-EM
ROUND NEW CONCEPT GARAGE AND CEILING LIGHTS
WITH SENSOR & EMERGENCY BACKUP BATTERY

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)



Ideal for indoor parking lots, commercial buildings, schools, warehouses, retail centers, apartment complexes. Designed for 9 to 16-foot mounting.


WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



15 1/6" (W) X 3 1/5" (H)

Features

- Stamped Galvanized Steel With Prismatic Polycarbonate Lens Redesigned For LED
- Designed for 9 to 16 Foot Mounting Heights
- Factory-Installed Options: Battery Backup, Motion Sensor
- 7-year Warranty

Technical Specification

Electrical:

- Wattage: 40W/60W/80W
- Input Current: 0.6A MAX
- Input Voltage: 120-277VAC 50/60Hz
- Power Factor: >0.90
- LPW: 135LPW

Mechanical:

- Stamped Galvanized Steel
- Twist-Lock Zhaga Socket Pre-Installed. See Motion Sensor Accessories
- Four 1/2" Threaded Hubs Located On Four Sides Of The Housing
- Prismatic Polycarbonate Lens
- Operating Temperature: -40°F ~ 104°F
- Suitable For Damp Locations
- 7-year Warranty

Emergency Battery Backup Spec:

- Output Power: 8W
- Output Voltage: 48V
- Li-Ion Battery / >90 Minutes Emergency Operation
- Test Button Installed on The Side of The Fixture

Lighting:

- MCTP: Multi-CCT and Power Switch Is In The Fixture
- Dimming: 0~10V Dimmable
- LED Type/ Brand: LUMILEDS 2835LED
- Total Lumens: 10800LM Max.
- Color Temperature: 3000K/4000K/5000K
- Color Rendering index: >70
- Beam Angle: 150°
- Lifespan: 70000 Hrs

Applications:

- Indoor Parking
- Commercial Buildings
- School
- Warehouses
- Complexes
- Apartment
- Garage

Other Models:




- 50W | 6750LM | CXER-30-50W-MCTP-SR-EM-WH



Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com |



Photometrics: CXER-40-80W-MCTP-SR-EM



BUD Rating: B2-U3-G2

Other Views:



Side View



Front View



Switch View

Performance Table: CXER-40-80W-MCTP-SR-EM

| MODEL NO. | Wattage | Voltage | Lumens | Color Temp. | BUG Rating | LPW |
|------------------------|---------|----------|---------|-------------|------------|-----|
| CXER-40-80W-MCTP-SR-EM | 40W | 120~277V | 5400LM | 3000K | B2-U3-G2 | 135 |
| | 60W | | 8100LM | 4000K | | |
| | 80W | | 10800LM | 5000K | | |

Sample Ordering

| Model | Min. | Max.Wattage | Color Temp. | Sensor | Battery |
|-------|------|-------------|-------------|--------|---------|
| CXER | 40 | 80W | MCTP | SR | EM |

Accessory:

Blank = No Option For Accessories
 WEC-3PR-72-TLB-BK = 600W Max, ZHAGA 12-24VDC PIR SENSOR, WITH
 BASE (OPTIONAL REMOTE CONTROL WEC-3RC)

Accessory:



WEC-3PR-72-TLB-BK

