

DAB SERIES Outdoor Lighting

DAB-B23-80-150W-MCTP-SR
23" DESIGNER AREA BELL LIGHT SYSTEM

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)




Ideal for airports, auto dealerships, corporate offices, education, government, healthcare, industrial warehouses, municipal parking, gas stations, convenient stores, recreation and public venues, restaurants, hospitality, retail and grocery stores.

Customer Name: _____

Project Name: _____

Note: _____

Type: _____



Features

- AL1060 Aluminum Hosing, Outdoor Powder Coating
- 7-Year Warranty
- Multi CCT and Power: Selectable Switch Inside Of The Fixture

Technical Specifications

Electrical:

- Voltage: 100-277V AC 50/60Hz
- Wattage: 80W/100W/150W
- Power Factor: 0.9
- THD<20%
- Efficacy: 130LM/W

Mechanical:

- AL1060 Aluminum Hosing, Outdoor Powder Coating
- Photocell Included (With Disconnect Switch) Twist-Lock Zhaga Socket Pre-Installed. See Motion
- Sensor Accessories.
- 6' SJTW 18,3 AWG Power Cable
- 6' SJTW Dimming Cable
- Aluminum LED board: High Conductive, Waterproof, Aging Resistance, Salt eResistance
- Programmable Bi-Level Motion Sensor & Emergency Backup Options
- Operating Temperature: -40°F~104°F
- IP Rating: IP66, Suitable for Wet Locations
- 7-Year Warranty

Lighting:

- Multi CCT and Power: Selectable Switch Inside Of The Fixture
- Dimmable: 0~10V Dimming
- Lens: High Light Transmittance PC, anti-UV and Fire Resistant
- LED: Lumileds 2835
- Total Lumens: 19500LM Max.
- Color Temperature: 3000K/4000K/5000K
- Color Rendering index: >70
- Beam Angle: Type V (150° X 150°)
- Lifespan: 70000 Hrs.

Applications:


- Ideal For Garden, Amusement Park, Residential Quater , Industrial Park And Pedestrian street.

Other Models:


- 100W | 13000LM | DAB-A16-50-100W-MCTP-SR
- 100W | 13000LM | DAB-B20-50-100W-MCTP-SR



Photometrics: DAB-B23-80-150W-MCTP-SR



BUD Rating: B3-U0-G2



80W 5000K, Area 45'x 65' Mounting Height: 9'

Performance Table: DAB-B23-80-150W-MCTP-SR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
DAB-B23-80-150W-MCTP-SR	80W 100W 150W	120-277V	10400LM 13000LM 19500LM	3000K 4000K 5000K	B3-U0-G2	130

Sample Ordering

Model	Size	Watt	Max. Watt	Color Temp.	Sensor Ready
DAB	B23	80	150W	MCTP	SR


Accessories:

Blank = No Option
DAB-BA = DAB BELL ARM FOR MOUNTING ON SINGLE OR DOUBLE POLE ADAPTER, BLACK
DAB-PB-B = DAB DECORATIVE STRAIGHT POLE BRACKET MODEL B, FOR FLAT OR ROUND POLES, BLACK
DAB-WB-A = DAB STRAIGHT WALL BRACKET MODEL A, BLACK
DAB-PA2-1 = DAB 2in POLE ADAPTER FOR 1 BELL ARM, BLACK
DAB-PA2-2 = DAB 2in POLE ADAPTER FOR 2 BELL ARM, BLACK
DAB-PA3-1 = DAB 3in POLE ADAPTER FOR 1 BELL ARM, BLACK
DAB-PA3-2 = DAB 3in POLE ADAPTER FOR 2 BELL ARM, BLACK
DAB-PA4-1 = DAB 4in POLE ADAPTER FOR 1 BELL ARM, BLACK
DAB-PA4-2 = DAB 4in POLE ADAPTER FOR 2 BELL ARM, BLACK
DAB-WB-C = DAB BENT DECORATIVE WALL BRACKET MODEL C, BLACK
WEC-3MR-72-TLB-BK = 600W Max, ZHAGA 12-24VDC PIR SENSOR, BLACK, WITH BASE (OPTIONAL REMOTE CONTROL WEC-3RC)
WEC-3MBT-72-TLB-BK = 600W Max, ZHAGA 12-24VDC PIR SENSOR, BLACK, WITH BASE (OPTIONAL REMOTE CONTROL WEC-3RC)


Factory Installed Options:

Blank = No Option
OPT-EM-OD2INT = INTERNAL EMERGENCY BACK UP BATTERY
OPT-3MPC = MICROWAVE PHOTOCELL
OPT-CLR-95(BK/GR/SR/WH) = COLOR PAINT

ACCESSORIES:



FACTORY INSTALLED OPTIONS:



ACCESSORIES:




**DAB-BA
DAB-PA2-2**
2in POLE + 23in fixture
(double)




**DAB-BA
DAB-PA3-2**
3in POLE + 23in fixture
(double)




**DAB-BA
DAB-PA4-2**
4in POLE + 23in fixture
(double)



DAB-PA2-2
2 1/4"(W) x 6 1/8"(H)



DAB-PA3-2
3 1/2"(W) x 6 1/8"(H)



DAB-PA4-2
4 3/4"(W) x 7"(H)




**DAB-BA
DAB-PA2-1**
2in POLE + 23in fixture




**DAB-BA
DAB-PA3-1**
3in POLE + 23in fixture




**DAB-BA
DAB-PA4-1**
4in POLE + 23in fixture



DAB-PA2-1
2 1/4"(W) x 5 3/4"(H)



DAB-PA3-1
3 1/2"(W) x 6"(H)



DAB-PA4-1
4 3/4"(W) x 7"(H)




DAB-BA
2in POLE + 23in fixture head



DAB-BA
3in POLE + 23in fixture head




DAB-BA
4in POLE + 23in fixture head



DAB-BA
23 1/2"(W) x 25 1/2"(H)



DAB-WB-A
DAB-WB-A+23in fixture
for wall




DAB-WB-A



DAB-PB-B
DAB-PB-B+23in fixture
for pole




DAB-PB-B
DAB-PB-B+23in fixture
(double)
for pole



DAB-PB-B
20 3/4"(W) x 7 1/2"(H)



DAB-WB-C
DAB-WB-C+23in fixture
for wall






DAB-WB-C
26"(W) x 31"(H) x 5"(D)




*Decorative Arms & Poles Available Per Job Spec






EPA Rating:

EPA of DAB Series

The height of the pole DAB-A16-50-100W- MCTP-SR	10'	12'	14'	16'	18'	20'
		4	4.47	4.94	5.41	5.88
	3.49	3.96	4.43	4.9	5.37	5.84
	5.6	6.07	6.54	7.01	7.48	7.95

The height of the pole DAB-B20-50-100W- MCTP-SR	10'	12'	14'	16'	18'	20'
		4.13	4.6	5.07	5.54	6.01
	3.56	4.03	5.5	5.97	6.44	6.91
	5.86	6.33	6.8	7.27	7.74	8.21

The height of the pole DAB-B23-80-150W- MCTP-SR	10'	12'	14'	16'	18'	20'
		4.54	5.01	5.48	5.95	6.42
	3.91	4.38	4.85	5.32	5.79	6.26
	6.74	7.21	7.68	8.15	8.62	9.09



COLOR CHART: * Choose from one of our Premium Colors with no set-up fee.

Gloss:



Hammer:



Texture:



Vein:

