

JOB NAME:	
DATE: _	
TYPE:	



FDL-18-30W-40K FDL-18-30W-30K

# **LED DRUM FIXTURES**

The LED Flush Mount Surface Fixture is a low profile downlight intended for ceiling or wall mount applications. Driver on Board (DOB) technology, with no driver or transformer needed. These flush mount ceiling lights mount directly to a 4" deep dish junction box. Ideal for Residential and commercial applications.

# **ELECTRICAL SPECIFICATIONS:**

Voltage: 120VACWattage: 30WPower factor: >0.90Efficacy: 73LM/W

## **HOUSING SPECIFICATIONS:**

- Construction: Spun aluminum + steel (brushed nickel finish)
- Gasket: closed cell Neoprene foam gasket
- Suitable for damp locations when gasket is used
- Maximum Ambient temperature: 104°F

### **CERTIFICATIONS: ETL**


















3-1/2"(H) X 18"(D)



MODEL	WATTS	VOLTAGE	LUMENS	COLOR TEMP
FDL-18-30W-40K	30W	120VAC	2200LM	4000K
FDL-18-30W-30K	30W	120VAC	2200LM	3000K

### **LIGHTING SPECIFICATIONS:**

- Dimming: Dimmable down to 10% using an approved dimmer
- Optics: white translucent acrylic lens
- LED: Seoul DOB (Driver On Board) Technology
- Total lumens: 2200LM
- Color temperature: 4000K/3000K
- CRI: >80

**WARRANTY:** 5 years