

FLVX SERIES

OUTDOOR LIGHTING

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

FLVX-LG-30-50W-MCTP-BR

FLVX-LG-30-50W-MCTP-BK

MCTP Multi Color Temperature & Multi Power/Wattage (Selectable)



Avail Finish:




Customer Name: _____

Project Name: _____

Note: _____

Type: _____



14 4/5" (H) x 4 1/6" (W) x 8 1/3" (D)

The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Features

- Die-cast Aluminum Housing with Powder Coat Finish (Black & Bronze)
- 1/2" Threaded Knuckle Stem
- 7-Year Warranty
- Lens Type: Plaid Tempered Glass + Aluminum Reflectors

Technical Specifications

Electrical:

- Voltage: 12V AC/DC
- Power Factor: >0.9
- Wattage: 30W/40W/50W
- Input current: 1A Max
- Efficacy: 95LPW

Mechanical:

- Die-cast Aluminum Housing with Powder Coat Finish (Black & Bronze)
- Solid State Lighting Technology for Long Life, No Maintenance Needed and High-Efficiency
- High Conductive Aluminum LED Board
- 8-1/2" PC Spike Included
- 1/2" Threaded Knuckle Stem
- IP Rating: IP65
- Operating Temperature: -40°F to 104°F
- Suitable for Wet Locations
- Rotatable Shroud with Set Screw
- 7-Year Warranty

Lighting:

- Dimmable: Non Dimmable
- Total lumens: 4750LM Max.
- Color Temperatures: 3000K/4000K/5000K
- Color Rendering Index: CRI ≥ 80
- Beam Angle: 60°
- Lifespan: 70,000 Hrs.

Applications:

- The fixture has classic traditional appearance, professional light distribution design, 90-degree beam angle, ideal for park landscaping, garden, architectural landscape lighting, suitable for wet locations

Other Models:

- 24W | 2900LM | FLVX-MD-24W-30K-BR
- 24W | 2900LM | FLVX-MD-24W-40K-BR




Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com




WG-07072022

Photometrics: FLVX-LG-30-50W-MCTP



BUG Rating: B2-U0-G0



24W 3000K, Area 30'x 30' Mounting Height: 9'

Other Views:

FLVX-LG-30-50W-MCTP-BR



Side View



Front View



Back View

FLVX-LG-30-50W-MCTP-BK



Side View



Front View



Back View

Performance Table: FLVX-LG-30-50W-MCTP

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FLVX-LG-30-50W-MCTP-BK	30W	12V	2850LM	3000K	B2-U0-G0	95
	40W		3800LM	4000K		
FLVX-LG-30-50W-MCTP-BR	50W		4750LM	5000K		

Sample Ordering

Model Size Watt Watt Color Temp. Finish

FLVX - LG - 30 - 50W - MCTP -

BK = Black
BR = Bronze

Accessories:

- Blank = No Option For Accessories
- A-41-BR = 1/2" NPT Hub, Cast Aluminum, Bronze Powder Coat Finish
- LSWN1 = Bag of 24, Waterproof Wire Connectors, For Up to Two 14-2 + One 16-2 Cables
- LSWN2 = Box of 24, Waterproof Wire Connectors, For Up to Three 12-2 Cables
- LSWN2-100 = Jar of 100, Waterproof Wire Connectors, For Up to Three 12-2 Cables
- A-41-S = Tree Mounting Base
- LG-SMB-BZ = 12V Brass Landscape Tree or Surface Bracket, Antique Bronze Finish
- BC-13 = 13" Bungee Cords with Hooks
- BC-18 = 18" Bungee Cords with Hooks
- BC-24 = 24" Bungee Cords with Hooks
- BC-32 = 32" Bungee Cords with Hooks

ACCESSORIES:



A-41-BR
1/2" NPT hub, Cast aluminum, Bronze Powder coat finish



LSWN1
Bag of 24, Waterproof wire connectors, for up to two 14-2 + one 16-2 cables



LSWN2
Box of 24, Waterproof wire connectors, for up to three 12-2 cables



LSWN2-100
Jar of 100, Waterproof wire connectors, for up to three 12-2 cables



A-41-S
Tree mounting base



LG-SMB-BZ
12V brass landscape tree or surface bracket, antique bronze finish



BC-13/18/24/32
13"/18"/24"/32" Bungee cords with hooks

