


FML SERIES Residential Lighting

FML-R12-MCT5-UGR
FLUSH MOUNT SERIES, UGR<19 LOW-GLARE
MCT5 Multi Color Temperature (Selectable)

Customer Name: _____
Project Name: _____
Note: _____ | Type: _____



12" x 1"

Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

Features

- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Die-cast Aluminum. Powder-Coated
- 5-Year Warranty
- 1" Deep

Technical Specifications

Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 22W
- Efficacy: 70 LPW

Mechanical:

- White Finish
- Exceptional Visual Comfort With UGR<19, Ensuring Low-Glare Illumination
- Die-cast Aluminum. Powder-Coated
- Maximum Ambient Temperature: 104°F
- 5-Year Warranty

Lighting:

- Lens: White translucent acrylic lens
- LED: Edge Lit LED Technology
- Dimming: TRIAC Dimming (Using Standard TRIAC LED Dimmers)
- Total Lumens: 1540LM
- Color Temperatures: 32700K/3000K/3500K/4000K/5000K
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Color Rendering Index: CRI ≥ 90
- Rated life: 50,000 hrs

Applications:



- Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

Other Models:


• 11W | 700LM | FML-R6-MCT-UGR • 14W | 980LM | FML-R8-MCT5-UGR • 17W | 1190LM | FML-R10-MCT5-UGR • 30W | 2100LM | FML-R18-MCT5-UGR



Photometrics: FML-R12-MCT5-UGR



BUG Rating: B1-U1-G1




Simulation Based on 4000K Area 40' x 40' Mounting Height: 9'

Other Views:



Side View



Front View



Back View

Performance Table: FML-R12-MCT5-UGR

MODEL NO.	Wattage	Voltage	Lumens	Color Temp.	BUG Rating	LPW
FML-R12-MCT5-UGR	22W	120V	1540LM	2700K 3000K 3500K 4000K 5000K	B1-U1-G1	70

Sample Ordering

Model Size Color Temp.

FML - R12 - MCT - UGR

Accessory:

Blank = No Option For Accessories

FML-RK-712 = 7in/12in ROD KIT FOR FML SEMI-FLUSH INSTALLATIONS
BOTH LENGTHS PROVIDED IN THE KIT TO CHOOSE

FML-SK6 = 6FT ADJUSTABLE SUSPENSION KIT FOR 18IN AND LARGER FML SERIES

ACCESSORIES:



FML-RK-712

7in/12in ROD KIT FOR FML SEMI-FLUSH INSTALLATIONS
BOTH LENGTHS PROVIDED IN THE KIT TO CHOOSE



FML-SK6

6' ADJUSTABLE SUSPENSION CABLE WITH CANOPY AND POWER CORD

