



**DIMENSIONS:**

**FML-R6-11W-30K**  
**FML-R6-11W-50K**

**LED FLUSH MOUNT SURFACE FIXTURE (6")**

The LED Flush Mount Surface Fixture is a low profile downlight intended for ceiling or wall mount applications. Driver on Board (DOB) technology, with no driver or transformer needed. These flush mount ceiling lights mount directly to a 4" deep dish junction box. provides general LED illumination in residential and light commercial applications.

**FEATURES:**

- Driver on Board Technology provides a 120V alternating current source and eliminates the need for traditional LED driver.
- Quick and easy to install on standard junction box, wall or ceiling mount with mounting plate
- Die-cast aluminum housing, high transmittance lens allowing for smooth, comfortable light pattern

**ELECTRICAL SPECIFICATIONS:**

- Voltage: 120V AC
- Wattage: 11W
- Lumens: 550LM
- Color Temperatures: 3000K and 5000K
- Maximum Ambient Temperature: 104°F
- CRI: 90+
- Power Factor: 0.95

MODEL	WATTS	VOLTS	LUMENS	COLOR TEMP
FML-R6-11W-30K	11W	120V	550LM	3000K
FML-R6-11W-50K	11W	120V	550LM	5000K

**LIGHTING SPECIFICATIONS:**

- Dimmable down to 10% using an approved dimmer
- LED: Epistar
- Life span: 50,000 hours
- Suitable for Damp Locations when gasket

**HOUSING SPECIFICATIONS:**

- Housing: Die-cast aluminum
- Finish: Powder coated white
- Diffuser: Matte white polycarbonate
- Gasket: Close cell Neoprene foam gasket
- Optics: White translucent acrylic lens

**WARRANTY:** 5 years

**CERTIFICATIONS:**

