# FML SERIES Residential Lighting

WESTGATE
THE FUTURE IS HERE...AND IT'S QUITE BRIGHT!

FML-R6-MCT

Customer Name:

Project Name:

Note: | Type:



MCT Selection:




6” x 1”

Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications.

## Features

- Unique DOB (Driver On Board) LED Board Enclosed in Clear PC Cover for Better Wet Location Performance
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Die-cast Aluminum. Powder-Coated
- 5-Year Warranty
- 1” Deep

## Technical Specifications

### Electrical:

- Voltage: 120V AC
- Power Factor: >0.90
- Wattage: 11W
- Efficacy: 60 LPW

### Mechanical:

- White Finish
- Die-cast Aluminum. Powder-Coated
- Maximum Ambient Temperature: 104°F
- Suitable For Damp Location

### Lighting:

- Lens: White translucent acrylic lens
- LED: Edge Lit LED Technology
- Dimming: TRIAC Dimming (Using Standard TRIAC
- LED Dimmers)
- Total Lumens: 660LM
- Color Temperatures: 3000K/ 4000K/ 5000K
- Multi CCT (Selectable Switch on LED Board Under the Lens)
- Color Rendering Index: CRI ≥ 90
- Rated life: 50,000 hrs

### Applications:

- Flush Mount lighting can use in most rooms of the house, especially those where you want ambient, general light. It's especially useful for hallways, kitchens, family rooms, bathrooms, closets, and bedrooms. Also Ideal for closets, storage areas, attics, corridors, or general lighting solutions for residential and commercial applications

### Other Models:

• 14W | 840LM | FML-R8-MCT • 17W | 1020LM | FML-R10-MCT • 26W | 1560LM | FML-R14-MCT • 30W | 2100LM | FML-R18-MCT • 45W | 2700LM | FML-R22-MCT

ENERGY STAR DIMMING 5 YEAR

Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com

## Photometrics: FML-R6-MCT






BUG Rating: B0-U1-G0




Simulation Based on 4000K Area 30'x 30' Mounting Height: 9'

## Other Views:



Side View



Front View



Back View

## Performance Table: FML-R6-MCT

| MODEL NO. | Wattage | Voltage | Lumens | Color Temp. | BUG Rating | LPW |
|---|---|---|---|---|---|---|
| FML-R6-MCT | 11W | 120V | 660LM | 3000K/ 4000K/ 5000K | B0-U1-G0 | 60 |

## Sample Ordering

| Model | | Size | | Color Temp. |
|---|---|---|---|---|
| FML | - | R6 | - | MCT |

## Accessory:

**Blank** = No Option For Accessories
**FML-R6-TRM-BK** = 6" ROUND TRIM FOR FML-R6 SERIES, BLACK FINISH
**FML-R6-TRM-BN** = 6" ROUND TRIM FOR FML-R6 SERIES, BRUSHED NICKEL FINISH
**FML-R6-TRM-BR** = 6" ROUND TRIM FOR FML-R6 SERIES, BRONZE FINISH
**OPT-EM-DLS6** = EMERGENCY BACKUP BATTERY MOUNT IN EXTENDED BASE, 1.3" HEIGHT

## ACCESSORIES:

**Optional Round Trims Fit Over the Fixture**



**FML-R6-TRM-BK**
BLACK FINISH



**FML-R6-TRM-BN**
BRUSHED NICKEL FINISH



**FML-R6-TRM-BR**
BRONZE FINISH



**OPT-EM-DLS6**
MOUNT IN EXTENDED BASE

## Example:

1. **FML-R6-MCT** (FOR FML R6 MCT FIXTURE 120-277V)

2. **FML-R6-MCT**
   **FML-R6-TRM-BK**
   (FOR FML R6 MCT FIXTURE 120-277V)
   (6" ROUND TRIM FOR FML-R6 SERIES, BLACK FINISH)


Phone: (877) 805-2252 | Fax: (877) 805-2252
www.westgatemfg.com